

GIBSON-HOMANS CO -- FIBERED ROOF COATING -- 5610-00-171-4722

===== Product Identification =====

Product ID:FIBERED ROOF COATING

MSDS Date:10/10/1990

FSC:5610

NIIN:00-171-4722

MSDS Number: CDVFP

=== Responsible Party ===

Company Name:GIBSON-HOMANS CO

Address:1755 ENTERPRISE PARKWAY

City:TWINSBURG

State:OH

ZIP:44087

Country:US

Info Phone Num:216-425-3255 OR 216-467-8128

Emergency Phone Num:216-425-3255 OR 216-467-8128

CAGE:33394

=== Contractor Identification

===

Company Name:GIBSON-HOMANS CO

Address:1623 E EUCLID AVE

Box:City:DES MOINES

State:IA

ZIP:50316

Country:US

Phone:515-262-9396

CAGE:33394

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 40-70%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:VOC = >300 G/L

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT EST.

===== Hazards Identifi

cation =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-SKIN: MAY CAUSE IRRITATION.
EYES: MAY CAUSE IRRITATIONBLURRED VISION. INHAL: EXCESSIVE
BREATHING OF HIGH VAPOR CONCENTRATIONS CAN CAUSE NASAL &
RESPIRATORY IRRITATION, DIZZINESS, NAUSEA, POSSIBL E
UNCONSCIOUSNESS, ASPHYXIATION. INGEST: CAN CAUSE GI IRRIT, NAUSEA,
VOMIT, DIARRHEA.

=====

===== First Aid Measures =====

First Aid:SKIN: WASH WITH SOAP & WATER. EYES: FLUSH WITH LARGE AMOUNTS
OF WATER. INHAL: REMOVE FROM AFFECTED AREA. IF BREATHING IS
DIFFICULT, GIVE OXYGEN. IF BREATHING HAS STOPPED, GIVE ARTIF RESP.
INGEST: DONT INDUCE VOMIT. SEE A DOCTOR IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:105F,41C
Lower Limits:0.8
Upper Limits:7.0
Extinguishing Media:USE CARBON DIO
XIDE, FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR A SELF CONTAINED BREATHING APPARATUS.
WATER MAY CAUSE FROTHING, APPLY CAUTIOUSLY.
Unusual Fire/Explosion Hazard:KEEP AWAY FROM SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE SPILL AREA. RECOVER FREE LIQUID. ADD
ABSORBENT TO SPILL AREA. REMOVE SOURCES OF IGNITION. VENTILATE AREA
IF NEEDED.
Neutralizing Agent:NA

===== Handling and Storag
e =====

Handling and Storage Precautions:KEEP AWAY FROM IGNIT SOURCES. USE ONLY
WITH ADEQUATE VENT. AVOID PROLONGED/REPEATED CONTACT W/SKIN.
Other Precautions:KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED, USE NIOSH/MSHA APPROVED
BREATHING APPARATUS.
Ventilation:MAINTAIN EXPOSURE BELOW TLV LEVEL.
Protective Gloves:SOLVENT RESISTANT.
Eye Protection:CHEMICAL GOGGLES.
Other Pr

Protective Equipment:NA

Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING. LAUNDER BEFORE REUSE.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:300 TO 315F

Vapor Pres:2MM

Vapor Density:>1

Spec Gravity:1.0

pH:NA

Evaporation Rate & Reference: