DEVOE COATINGS COMPANY -- DEVFLEX 601 595A24516 CLIPPER BLUE #601S5916 8010-01-208-7773

Product ID:DEVFLEX 601 595A24516 CLIPPER BLUE #601S5916 MSDS Date:10/08/1996 FSC:8010 NIIN:01-208-7773 MSDS Number: CDVRX === Responsible Party === Company Name: DEVOE COATINGS COMPANY Address:4000 DUPONT CIRCLE Box:7600 City:LOUISVILLE State:KY ZIP:40207 Country:US Info Phone Num:502-897-9861 Emergency Phone Num:800-424-9300 (CHEMTREC) Preparer's Name:LOUIS F HOLZKNECHT CAGE:1HK86 === Contractor Identification === Company Name: DEVOE COATINGS CO Address:4000 DUPONT CIRCLE Box:7600 City:LOUISVILLE State:KY ZIP:40207-4802 Country:US Phone:502-897-9861 CAGE:1HK86 Ingred Name: ACRYLIC RESIN Fraction by Wt: 5.0% Other REC Limits:NONE RECOMMENDED

Ingred Name:ANTIMONY TRIOXIDE (SARA III) CAS:1309-64-4 RTECS #:CC5650000 Fraction by Wt: 5.0% Other REC Limits:NONE REC OMMENDED OSHA PEL:0.5 MG/M3 ACGIH TLV:0.5 MG/M3 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:CHLOROHYDROCARBON POLYMER CAS:9002-86-2 RTECS #:KV0350000 Fraction by Wt: 5.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG/M3 TDUST

Ingred Name:DIPROPYLENE GLYCOL MONO METHYL ETHER (VAPOR PRESSURE 15 MINUTES. CONSULT A PHYSICIAN FOR MEDICAL

TREATMENT. SKIN: REMOVE WITH SOAP AND WATER. REMOVE SOILED CLOTHING. INGEST : DRINK 1 OR 2 GLASSES OF WATER. DONT INDUCE VOMIT. CALL DR. T REAT SYMPTOMATICALLY.

Spill Release Procedures: WASH WITH WATER. CONTAIN SPILLED MATERIAL AND REMOVE WITH INERT ABSORBENT. STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED OF.

Handling and Storage Precautions:STORE BELOW 110F AND KEEP FROM FREEZING. KEEP CONTAINER C LOSED WHEN NOT IN USE. DO NOT REUSE EMPTY CONTAINERS. Other Precautions: DO NOT TRANSFER CONTENTS TO BOTTLES OR OTHER UNLABELLED CONTAINERS. KEEP OUT OF REACH OF CHILDREN. Respiratory Protection: NO VAPOR/SPRAY/DUST BREATHING. FOR OUTDOOR OR SANDING/GRINDING: MECHANICAL FILTER RESPIRATOR. IN RESTRICTED VENT AREAS: CHEMICAL/MECHANICAL FILTERS, (PARTICULATE/VAPORS). IN CONFINED AREAS: AIR SUPPLI ED RESPIRATOR/H OOD. USE NIOSH/MSHA EQUIP Ventilation: GENERAL DILUTION OR LOCAL EXHAUST VENT TO KEEP BELOW LIMITS. Protective Gloves:RECOMMENDED Eye Protection: SPLASH GUARD W/SIDESHIELD. Other Protective Equipment:NONE REQUIRED Work Hygienic Practices: REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING WASHROOM. Supplemental Safety and Health NK Boiling Pt:B.P. Text:212 TO 356F Vapor Density:>AIR Spec Gravity:1.2 - 1.3 VOC Pounds/Gallon:231 pH:5-8 Solubility in Water: APPRECIABLE Appearance and Odor: CLIPPER BLUE VISCOUS LIQUID, MILD ODOR Percent Volatiles by Volume:59.87 Stability Indicator/Materials to Avoid:YES NK Hazardous Decomposition Products:CO, CO2, OXIDES OF NITROGEN, CHLORINE OR HCL. OXIDES & CHLORIDES OF ANTIMONY.

Waste Disposal Methods

IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims

all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.