

FABER CASTELL CORP -- UNI-PAINT MARKERS PX-20 -- 7520-01-207-4161

===== Product Identification =====

Product ID:UNI-PAINT MARKERS PX-20

MSDS Date:04/18/1991

FSC:7520

NIIN:01-207-4161

MSDS Number: CFDFL

=== Responsible Party ===

Company Name:FABER CASTELL CORP

Address:551 SPRING PLACE ROAD

Box:330

City:LEWISBURG

State:TN

ZIP:37091-3447

Country:US

Info Phone Num:615-359-1583

Emergency Phone Num:615-

359-1583

Preparer's Name:ANDREW TOROK

CAGE:32988

=== Contractor Identification ===

Company Name:FABER CASTELL CORP

Address:551 SPRING PLACE ROAD

Box:330

City:LEWISBURG

State:TN

ZIP:37091-3447

Country:US

Phone:615-359-1583

CAGE:32988

===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 75.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:NOT EST.

EPA Rpt Qty:1

000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL: IRRITATION TO NOSE/THROAT.
EYES: IRRITATION. MAY CAUSE DIZZINESS, DROWSINESS, &
UNCONSCIOUSNESS.
Medical Cond Aggravated by Exposure:NOT EST.

===== First Aid Measures =====

First Aid:INHAL: MOVE TO FRES
H AIR. GIVE ARTIFICIAL RESPIRATION. EYE:
FLUSH W/WATER. SKIN: WASH W/SOAP & WATER. INGEST: DONT INDUCE
VOMIT, CALL DR.

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:84.0F,28.9C
Autoignition Temp:Autoignition Temp Text:986F
Lower Limits:1.1
Upper Limits:6.4
Extinguishing Media:CO2, OR FOAM.
Fire Fighting Procedures:DONT USE WATER.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====
==

Spill Release Procedures:TREAT AS FLAMMABLE SOLVENT. USE ADEQUATE
VENTILATION.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM OPEN FLAME.
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE
Ventilation:YES
Protective Gloves:NONE
Eye Protection:NONE REQUIRED.
Other Protective Equipment:NONE
Work Hygienic Practices:WASH W/SOAP & WATER AFTER USE.
Supplementa

I Safety and Health
NK

===== Physical/Chemical Properties =====

HCC:F3
Boiling Pt:B.P. Text:104F,40C
Melt/Freeze Pt:M.P/F.P Text:NA
Vapor Pres:10.0
Vapor Density:3.7
Spec Gravity:0.89-0.91
Solubility in Water:INSOLUBLE.
Appearance and Odor:LIQUID INK, XYLENE ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Hazardous Decomposition Products:NONE

===== Dispos
al Considerations =====

Waste Disposal Methods:INCINERATE W/OTHER PETROLEUM PRODUCTS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice t
o verify and
assume responsibility for the suitability of this information to their
particular situation.