View NSN Online: https://aerobasegroup.com/nsn/8030-00-753-5008

## FLAMEMASTER CORP THE CHEM SEAL DIV -- CS 3204 PART A -- 8030-00-753-5008

Product ID:CS 3204 PART A MSDS Date:01/01/1996

FSC:8030

NIIN:00-753-5008

MSDS Number: CFJTD === Responsible Party ===

Company Name: FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352-4949 Country:US

Info Phone Num:818-982-1650 FAX 818-765-5603

Eme

rgency Phone Num:818-982-1650 Preparer's Name:HERBERT MOORE

CAGE:14439

=== Contractor Identification ===

Company Name: FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box: City: SUN VALLEY

State:CA

ZIP:91352-4949 Country:US

Phone:818-982-1650

CAGE:14439

======= Composition/Information on Ingredients ========

Ingred Name: METHYL BENZENE (TOLUENE) (SARA 313)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 10.0%

Other REC Limits: NONE SPECIFIED

OSHA PEL:50 PPM ACGIH TLV:50 PPM

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS
Ingred Name:VOC: 140 G/L RTECS #:999999VO Other REC Limits:NONE SPECIFIED
Ingred Name:LIQUID POLYSULFIDE POLYMER CAS:68611-50-7 Fraction by Wt: 55.0% Other REC Limits:NONE RECOMMENDED
======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:MAY CAUSE EYE, SKIN AND NOSE IRRITATION. MAY LEAD TO MUSCULAR WEAKNESS AND DIZZINESS. LONG TERM EXPOSURE MAY LEAD TO DERMATITIS, LIVER AND KIDNEY DAMAGE. HEADACHE NAUSEA & IMPAIRED COORDINATION. Medical Cond Aggravated by Exposure:SKIN DISORDERS, RESPIRATORY TRACT; LIVER OR KIDNEY DISEASE.
======================================
======================================
Flash Point Method:TCC Flash Point:90.0F,32.2C Autoignition Temp:Autoignition Temp Text:NA Lower Limits:1.3 Upper Limits:7.1 Extinguishing Media:DRY CHEMICAL, CO2, FOAM, WATER Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS (SCBA) IN CONFINED AREAS. Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND CAN TRAVEL TO SOURCES OF IGNITION.
=========== Accidental Release Measures ==============

Spill Release Procedures:REMOVE IGNI

TION SOURCES. TRANSFER TO SAFETY CONTAINER, CLEANUP REMAINDER. WASH AREA WITH SOAP & WATER.
=========== Handling and Storage ============
Handling and Storage Precautions:STORE IN COOL, WELL VENTILATED AREA. GROUND CONTAINERS WHEN FILLING OR EMPTYING.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:FOR VAPORS ABOVE 200 PPM USE SELF-CONTAINER BREATHING APPARATUS (SCBA).  Ventilation:LOCAL EXHAUST, HOOD; MECHANICAL GEN ERAL, FAN.  Protective Gloves:RUBBER Eye Protection:SAFETY GLASSES/FACE SHIELD  Other Protective Equipment:APPROPRIATE TO PREVENT PROLONGED CONTACT WITH SKIN.  Work Hygienic Practices:WASH HANDS BEFORE EATING, DRINKING OR SMOKING.
TRAIN PERSONNEL IN SAFE HANDLING OF THIS PRODUCT. Supplemental Safety and Health NA
======== Physical/Chemical Properties =========
Boiling Pt:B.P. Text:231F,111C Melt/Freeze Pt:M.P/F.P Text: