

PIMA VALVE INC -- MOBIL DTE OIL HEAVY MEDIUM -- 9150-00-993-8588

===== Product Identification =====

Product ID:MOBIL DTE OIL HEAVY MEDIUM

MSDS Date:12/07/1994

FSC:9150

NIIN:00-993-8588

MSDS Number: CFRFH

=== Responsible Party ===

Company Name:PIMA VALVE INC

Address:6525 W. ALLISON RD

Box:5010

City:CHANDLER

State:AZ

ZIP:85226-9405

Country:US

Info Phone Num:520-796-1095

Emergency Phone Num:520-796-1095

CAGE:MO457

=== Contractor Identification ===

Company Name:MO

BIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWS ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

Company Name:PIMA VALVE INC

Address:6525 W. ALLISON RD

Box:5010

City:CHANDLER

State:AZ

ZIP:85226-9405

Country:US

Phone:520-796-1095

CAGE:MO457

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE:0T5C6

===== Composition/Information on Ingredients =

=====

Ingred Name:PRODUCT IS NOT FORMULATED TO CONTAIN INGREDIENTS WHICH HAVE EXPOSURE LIMITS ESTABLISHED BY REGULATORY AGENCIES.

RTECS #:9999999ZZ

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >2000 MG/KG

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INGEST:PRACTICALLY NON-TOXIC.EYE'SKIN: PRAC

TICALLY NON-IRRITATING AND NON-SENSITIZING.INHAL:NO HAZARD EXPECTED.

Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.

Effects of Overexposure:NO SYMPTOMS ANTICIPATED.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.C

ALL PHYSICIAN IF

IRRITATION OCCURS.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:NOT EXPECTED TO BE A PROBLEM.IF MORE THAN 1 PINT IS INGESTED,DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION.IF CONSCIOUS,GIVE 1-2 GLASSES OF WATER.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>400F,>204C

Lower Limits:0.6

Upper Limits:7.0

Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE,FOAM.

Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIAL IN AN APPROPRIATE CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS.AVOID

RUNOFF INTO WATER WAYS.REPORT SPILLS RESULTING  
IN SHEEN UPON WATER TO 800-424-8802.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED  
PLACE. KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY FROM  
HEAT,SPARKS,FLAMES AND INCOMPATIBLE MATERIALS.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED IN NORMAL SERVICE.

Ventilation:USE GENERAL DILUTION VENTILATION.

Protective Gloves:NOT NEEDED IN NORMAL SERVICE.

Eye Protection:SAFETY GLASSES

Other Protective Equipment:PROVIDE A LOCAL EYE WASH STATION AND SAFETY  
SHOWER.

Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS  
PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.

Supplemental Safety and Health  
NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P.

Text:>600F,>316C

Vapor Pres:41CS@104F

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIQUID;LIGHT AMBER;MILD ODOR.

Percent Volatiles by Volume: