Product ID:NITROGEN MSDS Date:11/25/1985 FSC:3040 NIIN:01-278-5385 **MSDS Number: CFRHB** === Responsible Party === Company Name: AGA GAS INC Address:6225 OAKTREE BLVD City:CLEVELAND State:OH ZIP:44131 Country:US Info Phone Num:216-642-6600 Emergency Phone Num:216-642-6600 CAGE:0KPC9 === Contractor Identification === Company Name: AGA GAS INC Address:6225 OAKTREE BLVD Box:94737 City:CLEVE LAND State:OH ZIP:44101-4737 Country:US Phone:216-642-6600 CAGE:0KPC9 Company Name: KOCSIS BROS MACHINE CO Address:11720 S MAYFIELD AVE Box:City:WORTH State:IL ZIP:60482 Country:US Phone:312-597-8110 CAGE:73181

Ingred Name:NITROGEN CAS:7727-37-9 RTECS #:QW9700000 Other REC Limits:NONE RECOMMENDED ACGIH TLV:ASPHYXIANT; 9596

LD50 LC50 Mixture:NOT RELEVANT Rou tes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, CNS, RESPIRATORY TRACT. ACUTE- NITROGEN IS NONTOXIC BUT MAY PRODUCE SUFFOCATION BY DISPLACING OXYGEN. NO HARMFUL EFFECT EXPECTED FROM VAPOR. LIQUID CAN CAUSE FROSTBITE. THIS P RODUCT IS A GAS AT NORMAL TEMPERATURE AND PRESSURE. CANNOT BE SWALLOWED. CHRONIC- NONE. Explanation of Carcinogenicity:NONE Effects of Overexposu re:LOSS OF BALANCE OR DIZZINESS; TIGHTNESS IN THE FRONTAL AREA OF THE FOREHEAD; TINGLING OF THE TONGUE, FINGERTIPS OR TOES; WEAKENED SPEECH LEADING TO THE INABILITY TO UTTER SOUNDS;

RAPID REDUCTION IN TH E ABILITY TO PERFORM MOVEMENTS; REDUCEDCONSCIOUSNESS OF SURROUNDINGS; LOSS OF TACTILE SENSATIONS

Medical Cond Aggravated by Exposure:NONE

First Aid:PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVE

REXPOSURE. RESCUE PERSONNEL SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS. INHALED:REMOVE TO FRESH AIR. PROVIDE OXYGEN/CPR IF NEEDED. SKIN:TRE AT FOR FROSTBITE. USE LUKEWARM WATER. DO NOT USE HOT WATER. EYES:CONSULT AN OPHTHALMOLOGIST IMMEDIATELY.

Flash Point:NONE

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL FOR SURROUNDING FIRE. NITROGEN CANNOT CATCH FIRE. Fire Fighting Procedures :EVACUATE ALL PERSONNEL FROM DANGER AREA.

IMMEDIATELY DELUGE CONTAINERS WITH WATER SPRAY FROM MAXIMUM DISTANCE UNTIL COOL, THEN MOVE CONTAINERS AWAY IF NO RISK. Unusual Fire/Explosion Hazard:CYLINDERS MAY RUPTURE DUE TO HEAT OF FIRE. NO PART OF CYLINDER SHOULD BE SUBJECTED TO A TEMPERATURE HIGHER THAN 52C (125F). MOST CONTAINERS VENT WHEN HEATED.

Spill Release Procedures: USE APPROPRIATE PROTECTIVE EQUIPMENT. E

## VACUATE

ALL PERSONNEL. VENTILATE AREA. IF LEAK IS IN CONTAINER OR CONTAINER VALVE, CONTACT CHEMTREC AT (800-424-9300) FOR EMERGENCY ASSISTANCE. Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions: STORE IN COOL, DRY, VENTILATED AREA BELOW 125F (52C). KEEP OUT OF REACH OF SMALL CHILDREN. STORE UPRIGHT AND FIRMLY SECURED

Other Precautions: WASH HANDS AFTER HANDLING. NEVER CARRY A COMPRESSED GAS CYL

INDER IN AN ENCLOSED SPACE SUCH AS A CAR TRUNK, VAN OR STATION VAGON. USE ONLY IN WELL VENTILATED AREA. DO NOT DRAG, SLIDE OR ROLL CYLINDERS. USE A SUITABLE HAND TRUCK TO MOVE THEM.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection:NONE NORMALLY REQUIRED. IN EMERGENCIES, WEAR A NIOSH-APPROVED POSITIVE PRESSURE AIR LINE WITH MASK OR SELF-CONTAINED BREATHING APPARATUS. Ventilation:LOCAL EXHAUST Protective Gloves:ANY MATERIAL Eye Protection :SAFETY GLASSES OR GOGGLES Other Protective Equipment:SAFETY SHOES Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. Supplemental Safety and Health NONE

HCC:G3 NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:-320F,-196C Melt/Freeze Pt:M.P/F.P Text:-346F,-210C Vapor Density:0.97 Spec Gravity:NOT RELEVANT Evaporation Rate & amp; Reference:NOT RELEVANT Solubility in Water:VERY S

## LIGHT Appearance and Odor:COLORLESS, ODORLESS GAS

Stability Indicator/Materials to Avoid:YES NONE Stability Condition to Avoid:EXCESSIVE HEAT Hazardous Decomposition Products:NONE

Waste Disposal Methods:SLOWLY RELEASE INTO ATMOSPHERE OR RETURN IN THE SHIPPING CONTAINER PROPERLY LABELED, WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE. FOLLOW ALL LOCAL, STATE AND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.