

INLAND VACUUM INDUSTRIES INC -- INVOIL 940 -- 9150-00-930-4945

===== Product Identification =====

Product ID:INVOIL 940
MSDS Date:01/23/1996
FSC:9150
NIIN:00-930-4945
MSDS Number: CFYYG
=== Responsible Party ===
Company Name:INLAND VACUUM INDUSTRIES INC
Address:35 HOWARD AVE
Box:373-T
City:CHURCHVILLE
State:NY
ZIP:14428
Country:US
Info Phone Num:716-293-3330
Emergency Phone Num:716-293-3330
Prepar
er's Name:SANDRA J.EMLAMR
CAGE:59256
=== Contractor Identification ===
Company Name:INLAND VACUUM INDUSTRIES INC
Address:35 HOWARD AVE
Box:373
City:CHURCHVILLE
State:NY
ZIP:14428
Country:US
Phone:716-293-3330
CAGE:59256
Company Name:SDB CONSULTANTS LTD
Address:401 WHITNEY AVE SUITE 120
Box:City:GRETNA
State:LA
ZIP:70056
Country:US
Phone:504-366-9105
CAGE:0PGK2

===== Composition/Information on Ingredients =====

Ingred Name:TETRAMETHYL,TETRAPHENYL,TRISILOXANE (METHYLPHENYL SILI

CONE)
CAS:3982-82-9

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:MANUFACTURER STATES DETAILED STUDIES
HAVE NOT BEEN MADE BUT MATERIAL IS NOT EXPECTED TO BE DERMATITIC.
Effects of Overexposure:NONE KNOWN TO MFR;MAY IRRITATE EYES OR SKIN ON
PROLONGED CONTACT.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O2
IF
NEED;EYES/SKIN:FLUSH W LG AMTS H2O FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Extinguishing Media:CHEMICAL FOAM,CO2
Fire Fighting Procedures:USE NIOSH APPROVED SCBA IN FIRES AND IN
CONFINED AREA
Unusual Fire/Explosion Hazard:NONE NOTED BY THE MFR.

===== Accidental Release Measures =====

Spill Release P
rocedures:USE PROPER PERSONAL PROTECTION;USE SUITABLE
INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:NO SPECIAL PRECAUTION.STORE IN COOL
DRY AND GOOD VENTILATED AREA.KEEP CONTAINER TIGHTLY CLOSED.
Other Precautions:AVOID CONTACT WITH SKIN AND EYES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE REQUIRED UNDER NORMAL

USE.
Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION
Protective Gloves:OIL RESISTANT RUBBER
Eye Protection:GOGGLES OR SAFETY GLASSES W.SIDE SHIELDS
Other Protective Equipment:NONE SHOULD BE REQUIRED NORMAL USE.
Work Hygienic Practices:USED OIL FROM VACUUM PUMPS IS HOT (>122F,>50C).
AVOID SKIN CONTACT TO PREVENT BURNS.--SEE SUPPLEMENTAL S&H DATA--
Supplemental Safety and Health
WORK HYGENIC PRACTICES,CONTINUED:IF VACUUM PUMP IS USED TO PUMP CORROSIVE GASES,RE
SPIRATORS MAY BE REQUIRED BY PUMP MAINTENANCE PERSONNEL.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>392F,>200C
Spec Gravity:1.07
Evaporation Rate & Reference:NIL (BU AC=1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR TO PALE YELLOW TRANSPARENT, VISCOUS LIQUID, WITH NO ODOR.
Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS,ACIDS,ALKALIS
Stability Condition to Avoid:HEAT,FLAMES
Hazardous Decomposition Products:INCOMPLETE COMBUSTION PRODUCES CO.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States o

f America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.