

DEFT INC/CHEMICAL COATING DIV -- CAT, MIL-C-85285B, 26492, 04GY004CAT -- 8010-01-399-9419

===== Product Identification =====

Product ID:CAT, MIL-C-85285B, 26492, 04GY004CAT

MSDS Date:03/07/1996

FSC:8010

NIIN:01-399-9419

Kit Part:Y

MSDS Number: CGFKD

=== Responsible Party ===

Company Name:DEFT INC/CHEMICAL COATING DIV

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Info

Phone Num:714-474-0400

Emergency Phone Num:714-474-0400

Preparer's Name:NORM GAUL

CAGE:FO129

=== Contractor Identification ===

Company Name:DEFT INC/CHEMICAL COATING DIV

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Phone:714-474-0400

CAGE:FO129

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:C8 & 10 AROMATI

C HYDROCARBON, VAPOR PRESSURE 3 @ 68F

CAS:64742-95-6

RTECS #:WF3400000

Fraction by Wt: 5.0%

Other REC Limits:NOT RECOMMENED

Ingred Name:ALIPHATIC ISOCYANATE (NOTE: 3-6MTHS STORAGE, FREE MOMOMER
CONTENT MAY RISE, MAXIMUM OF 1.6%. MOBAY CEILING LEVEL 0.02)

CAS:28182-81-2

RTECS #:NQ9170000

Fraction by Wt: 90.0%

Other REC Limits:0.005PPM MFR RECOMED

Ingred Name:N-BUTYL ACETATE, VAPOR PRESSURE 13 @ 68F

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 5.0%

Other REC Limits:NOT RECOMMENED

OSHA PEL:

150PPM; STEL 200PPM

ACGIH TLV:150PPM; STEL 200PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL: RESPIRATORY TRACT & NS

DEPRESSION (HEADACHE, DIZZY, STAGGERING GAIT, CONFUSION,
UNCONSCIOUS, COMA). EYE: IRRIT, TEARING, REDNESS, SWELLING,
STINGING. SKIN: SWELLING, REDNESS,

RASH. INGEST: CORR OSIVE IN THE

MOUTH, STOMACH TISSUE, DIGESTIVE TRACT. VOMIT MAY CAUSE ASPIRATION
OF SOLVENT (CHEMICAL PNEUMONITIS).

Effects of Overexposure:SKIN: DRYING, DEFATTING, CRACKING. CHRONIC:
ISOCYANATE SENSITIZATION.

Medical Cond Aggravated by Exposure:ASTHMA & OTHER RESPIRATORY
DISORDERS, SKIN ALLERGIES, ECZEMA, DERMATITIS. ISOCYANATE
SENSITIZATION.

===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR. SKIN:

WASH W/SOAP & WATER. EYE:

FLUSH W/LUKEWARM WATER FOR 15 MINS. INGEST: DONT INDUCE VOMIT.

OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:76.0F,24.4C

Lower Limits:1.00

Upper Limits:7.60

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG,
WATER SPRAY.

Fire Fighting Procedures:WEAR SCBA & FULL PROTECTIVE EQUIPMENT. USE
WATER TO COOL CLOSED CONTAINERS.

Unusual Fire/Explo

sion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE
FROM HEAT & OTHER IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. REMOVE IGNITION SOURCES.
CONTAIN & REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID HIGH TEMP & OTHER IGNITION
SOURCES. STORE IN TIGHTLY CLOSED CONTAINERS & IN WELL VENTILATED
AR

EA.

Other Precautions:KEEP CONTAINERS TIGHT & UPRIGHT. SMOKE IN SMOKING
AREAS ONLY. DONT HANDLE UNTIL MANUFACTURERS SAFETY PRECAUTIONS HAVE
BEEN READ AND UNDERSTOOD.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN AN ORGANIC VAPOR ENVIRONMENT (AIR PURIFYING
OR FRESH AIR SUPPLIED). VAPOR PARTICULATE RESPIRATOR (TC23C
NIOSH/MSHA) MAY BE APPROPRIATE WHERE AIR MONITORING DEMONSTRATES
VAPOR LEVELS BELOW TEN TIMES EXPOSURE LIMITS.

Ve

ntilation:EXHAUST VENTILATION.
Protective Gloves:COTTON, NEOPRENE, RUBBER, POLYETHYLENE
Eye Protection:CHEM SPLASH GOGGLES/FACE/SIDE SHIELDS.
Other Protective Equipment:USE LONG SLEEVE & LEG CLOTHING.
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING & BEFORE EATING,
SMOKING, DRINKING. SMOKE IN SMOKING AREAS ONLY.
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:260F,127C
Vapor Density:>AIR
Spec Gravity:1.12845

VOC Pounds/Gallon:113
pH:NA
Evaporation Rate & Reference:0.44 X N-BUTYL ACETATE
Solubility in Water:INSOLUBLE
Appearance and Odor:AMBER LIQUID W/SOLVENT ODOR.
Percent Volatiles by Volume:25.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS & SURFACE ACTIVE
MATERIALS.
Stability Condition to Avoid:MOISTURE, MATERIAL WHICH REACT
W/ISOCYANATES & HIGH TEMPERATURES.
Haza
rdous Decomposition Products:CO, CO2, OXIDES OF NITROGEN, TRACES OF
HYDROGEN CYANIDE, HEXAMETHYLENE DIISOCYANIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE &
LOCAL REGULATIONS. EMPTY CONTAINERS HAVE PRODUCT RESIDUE &
FLAMMABLE VAPORS. DONT INCINERATE CLOSED CONTAINERS. EPA CODE:
D001, F003, F005. WASTE CHARACTERISTICS: IGNITABLE, REACTIVE.

===== Other Information =====

=====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to the
ir
particular situation.