

View NSN Online: <https://aerobasegroup.jp/nsn/8030-00-252-3391>

FEL-PRO CHEMICAL PRODUCTSS LP -- 216 PLIABLE GASKET SEALER/GS-2/PLI-A-SEAL --
8030-00-252-3391

===== Product Identification =====

Product ID:216 PLIABLE GASKET SEALER/GS-2/PLI-A-SEAL

MSDS Date:01/17/1997

FSC:8030

NIIN:00-252-3391

MSDS Number: CGJPC

=== Responsible Party ===

Company Name:FEL-PRO CHEMICAL PRODUCTSS LP

Address:3412 WEST TOUHY AVENUE

City:LINCOLNWOOD

State:IL

ZIP:60645-5000

Country:US

Info Phone Num:303-289-5651

Emergency Phone Num:303-289-5651

Preparer's Name:CATHY GRIFFITH

CAGE:GO402

=== Contractor Identification ===

Company Name:FEL-PRO CHEMICAL PRODUCTS DIV OF FELT PRODUCTS

Address:7450 N MCCORMICK

Box:1205

City:SKOKIE

State:IL

ZIP:60076-8205

Country:US

Phone:303-289-5651

CAGE:GO402

Company Name:FEL-PRO CHEMICAL PRODUCTS LP

Address:3412 WEST TOUHY AVE

Box:City:LINCOLNWOOD

State:IL

ZIP:60645

Country:US

Phone:303-289-5651

CAGE:05VH4

===== Composition/Information

on Ingredients =====

Ingred Name:ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL
CARBINOL (IARC-GROUP 3) *97-4*
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 10%
Other REC Limits:400 PPM
OSHA PEL:400 PPM
ACGIH TLV:400 PPM

Ingred Name:CLAY (KAOLIN), ALUMINUM SILICATE *97-4*
CAS:1332-58-7
RTECS #:GF1670500
Fraction by Wt: >3%
ACGIH TLV:10 MG/CUM TOTAL DUST

Ingred Name:CASTOR OIL, OXIDIZED *97-4*
CAS:68187-84-8
Fraction by Wt: >3%

Ingred Name:CALCIUM CARBONATE, DOMOLITE
, LIMESTONE, WHITING *97-4*
CAS:1317-65-3
RTECS #:EV9580000
Fraction by Wt: >3%
Other REC Limits:5 MG/M3 RESP DUST
OSHA PEL:15 MG/M3
ACGIH TLV:10 MG/CUM TOTAL DUST

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: >3%

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50(RAT): 5045 MG/KG ISOPROPANOL
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Ch

ronic:EYES: SEVERELY IRRITATING. SKIN: MILD
IRRITANT. INHALATION: HARMFUL, MAY CAUSE INJURY TO THE LUNGS,
LIVER/KIDNEYS & RESPIRATORY TRACT IRRITATION. INGESTION:
HARMFUL/FATAL.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:DROWSINESS, IRRITATION, INTOXICATION,
DEFATTING, REDNESS.

Medical Cond Aggravated by Exposure:PRE-EXISTING PULMONARY &
DERMATOLOGICAL DISORDERS.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/PL
ENTRY OF WATER FOR 15 MINS. SKIN: WASH W/SOAP
& WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF
NEEDED. INGESTION: DON'T INDUCE VOMITING. GIVE A GLASS OF
WATER/MILK. NEVER GI VE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:53F

Lower Limits:2.5

Upper Limits:12

Extinguishing Media:WATER FOG, CO2, DRY CHEMICAL, FOAM.

Fire Fighting

Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE
CLOTHING. USE WATER TO COOL EXPOSED CONTAINERS. WATER STREAM MAY
CAUSE FROTHING W/SUBSEQUENT SPREAD OF FLAME.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY RUPTURE/EXPLODE
W/EXTREME HEAT. VAPORS ARE > THAN AIR & TRAVEL ALONG GROUND TO
LOCATIONS DISTANT FROM IGNITION SOURCE/FLASHBACK.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION. DIKE/CONTAIN. WEA
R
APPROPRIATE PROTECTIVE EQUIPMENT DURING CLEANUP. ABSORB W/INERT
MATERIAL, SUCH AS CLAY. SWEEP/SHOVEL INTO LOOSELY-COVERED WASTE
CONTAINER & REMOVE TO APP ROPRIATE WASTE AREA.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS & FLAME.
KEEP CONTAINER CLOSED WHEN NOT IN USE. USE W/ADEQUATE VENTILATION.
GROUND & BOND CONTAINERS WHEN TRANSFERRING.
Other Precautions:KEEP OUT OF REACH OF CHILDREN. FOL

LOW ALL PRECAUTIONS

EVEN AFTER CONTAINER IS EMPTIED, PRODUCT MAY RETAIN RESIDUES. AVOID CONTACT W/EYES, SKIN & CLOTHING. FOR INDUSTRIAL USE ONLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV/PEL IS EXCEEDED, USE NIOSH APPROVED VAPOR CARTRIDGE RESPIRATOR.

Ventilation:LOCAL EXHAUST AS NEEDED.

Protective Gloves:BUTYL RUBBER

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER.

Work Hygie

nic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. FOLLOW GENERAL INDUSTRIAL SAFETY PRACTICES DURING USE.

Supplemental Safety and Health

DON'T SMOKE/EAT DURING USE. DON'T REUSE EMPTY CONTAINERS W/O COMMERCIAL CLEAN/RECONDITION.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:180F

Melt/Freeze Pt:M.P/F.P Text:>32F

Vapor Density:>1

Spec Gravity:1.25

VOC Pounds/Gallon:102

Evaporation Rate & Reference:SLOWER THAN BU AC

Solubility i

n Water:SLIGHT

Appearance and Odor:BLACK LIQUID W/ALCOHOL ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG LEWIS/MINERAL ACIDS, STRONG BASES/OXIDANTS. METALS, SURFACE-ACTIVE COMPOUNDS.

Stability Condition to Avoid:HEAT, SPARKS, FLAME, SOURCES OF IGNITION.

Hazardous Decomposition Products:OXIDES OF CARBON, AROMATIC & ALIPHATIC HYDROCARBONS.

===== Disposal Considerations =====

Wast

e Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL
REGULATIONS. FLAMMABLE, UN1133.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing
this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.