

LOCTITE CORP -- SUPERFLEX ULTRA BLUE (TM) SILICONE

=====
MSDS Safety Information
=====

FSC: 5330
NIIN: 01-247-2475
MSDS Date: 01/22/1996
MSDS Num: CGMKB
Product ID: SUPERFLEX ULTRA BLUE (TM) SILICONE
MFN: 01
Responsible Party
Cage: 7K128
Name: LOCTITE CORP
Address: 705 NORTH MOUNTAIN RD
City: NEWINGTON CT
06111
Info Phone Number: 203-278-1280
Emergency Phone Number: 203-278-1280
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 7K128
Name: LOCTITE CORP
Address: 705 N MT RD
City: NEWINGTON CT 06111
Phone: 312-689-6200
Cage: 05972
Name: LOCTITE CORPORATION
Address: 1001 TROUT BROOK CROSSING
City: ROCKY HILL CT 06067-3910
Phone: 860-571-5100

=====
Item Description Information
=====

Item Manager: S9I
Item Name: GASKET
Unit of Issue: EA
UI Container Qty: 1
Type of Container: UNKNOWN

=====
Ingredients
=====

Cas: 63148-62-9
RTECS #: VU6200000
Name: SF-96; (POLY (DIMETHYLSILOXANE))
% Wt: 15-20

Cas: 70131-67-8
Name: POLYDIMETHYLSILOXANE/DIMETHYL POLYSIL

OXANE

% Wt: 35-40

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Cas: 471-34-1

RTECS #: FF9335000

Name: CALCIUM CARBONATE

% Wt: 30-35

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 15 MG/M3

ACGIH TLV: 10 MG/M3

Cas: 68611-44-9

Name: SILANE, DICHLORODIMETHYL-, REACTION PRODUCTS WITH SILICA/MODIFIED SILICON
DIOXIDE

% Wt: 5-10

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV:

NOT ESTABLISHED

Cas: 2224-33-1

Name: VINYLTRI(METHYLETHYLKETOXIME)SILANE

% Wt: 3-5

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Name: SUBSTITUTES SILANE ESTERS

% Wt: 0.1-1

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Cas: 96-29-7

RTECS #: EL9275000

Name: METHYL ETHYL KETOXIME

% Wt: *****

Other REC Limits: NONE RECOMMENDE

D
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

=====
Health Hazards Data
=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: EYE AND SKIN IRRITANT. MODERATELY TOXIC BY INGESTION. WHEN HEATED TO TEMPERATURES ABOVE 300F IN THE PRESENCE OF AIR, THIS PRODUCT CAN

FORM FORMALDEHYDE VAPORS.

Explanation Of Carcinogenicity: FORMALDEHYDE IS A POTENTIAL CANCER HAZARD AND A KNOWN SKIN AND RESPIRATORY SENSITIZER.

Signs And Symptoms Of Overexposure: FORMALDEHYDE VAPORS IRRITATE EYES, NOSE AND THROAT. METHYL ETHYL KETOXIME PRODUCED DURING CURING IS TOXIC AND IRRITATES EYES, NOSE AND THROAT.

Medical Cond Aggravated By Exposure: DERMATITIS.

First Aid: INGESTION: DO NOT INDUCE VOMITING. KEEP INDIVIDUAL CALM. OBTAIN MEDICAL ATTENTION. INHALATION: RE

MOVE TO FRESH AIR. TREAT SYMPTOMATICALLY.

SKIN: WIPE OFF PASTE WITH PAPER TOWEL OR CLOTH. WASH EXPOSED AREA WITH SOAP AND WATER. EYE: FLUSH ATLEAST 15 MINUTES WITH WATER. OBTAIN MEDICAL ATTENTION.

=====
Handling and Disposal
=====

Spill Release Procedures: WIPE OR SCRAPE UP SPILLED MATERIAL MAINTAIN GOOD VENTILATION FOR LARGE SPILLS. PLACE SCRAP MATERIAL IN A WELL VENTILATED PLACE AND AL

LOW TO CURE TO RUBBER.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: CURED RUBBER CAN BE INCINERATED. FOLLOW FEDERAL, STATE, AND LOCAL REGULATIONS.

Handling And Storage Precautions: STORE IN A DRY AREA BELOW 90 F TO PRESERVE SHELF LIFE. KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID EYE OR SKIN CONTACT. AVOID BREATHING VAPOR.

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

=====
Fire and Explosion Hazard Infor

mation

Flash Point Method: TCC

Flash Point Text: >200F,93C

Extinguishing Media: CARBON DIOXIDE, FOAM, DRY CHEMICAL.

Fire Fighting Procedures: NONE SPECIFIED BY MANUFACTURER.

Unusual Fire/Explosion Hazard: NONE.

Control Measures

Respiratory Protection: NONE SPECIFIED BY MANUFACTURER.

Ventilation: PROVIDE LOCAL VENTILATION FOR
PROLONGED USE IN CONFINED AREA.

Protective Gloves: RUBBER OR PLASTIC GLOVES.

Eye Protection: SAFETY GLASSES OR GOGGLES.

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health: NONE SPECIFIED BY MANUFACTURER.

Physical/Chemical Properties

HCC: N1

Vapor Pres: <5

Vapor Density: 3.0

Spec Gravity

: 1.3

PH: 7-8

Solubility in Water: POLYMERIZED

Appearance and Odor: BLUE PASTE, MILD ODOR.

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: MOISTURE.

Materials To Avoid: POLYMERIZED BY CONTACT WITH MOISTURE.

Hazardous Decomposition Products: FORMALDEHYDE, SILICA FUME.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT.

Toxicological Information

Ecological Information

MSDS Transport Information

Regulatory Information

=====
=====
Other Information
=====
=====

Transportation Information
=====

Responsible Party Cage: 7K128
Trans ID NO: 118127
Product ID: SUPERFLEX ULTRA BLUE (TM) SILICONE
MSDS Prepared Date: 01/22/1996
Review Date: 04/08/1998
MFN: 1
Net Unit Weight: UNKNOWN
A
F MMAC Code: NR
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: EA
Container QTY: 1
Type Of Container: UNKNOWN
Additional Data: NOT REGULATED FOR TRANSPORTATION
=====

Detail DOT Information
=====

DOT PSN Code: ZZZ
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

Detail IMO Information
=====

IMO PSN Code: ZZZ
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION
=====

Detail IATA Information
=====

IATA PSN Code: ZZZ
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

Detail AFI Information
=====

AFI PSN Code: ZZZ
AF

I Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====

HAZCOM Label

=====

Product ID: SUPERFLEX ULTRA BLUE (TM) SILICONE

Cage: 7K128

Company Name: LOCTITE CORP

Street: 705 N MT RD

City: NEWINGTON CT

Zipcode: 06111

Health Emergency Phone: 203-278-1280

Label Required IND: Y

Date Of Label Review: 04/08/1998

Status Code: C

Label Date: 04/08/1998

Origination Code: F

Chronic Hazard

IND: Y

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: CAUTION

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: Slight

Reactivity Hazard: None

Hazard And Precautions: STORE IN A DRY AREA BELOW 90 F TO PRESERVE SHELF LIFE.

KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID EYE OR SKIN CONTACT. AVOID

BREATHING VAPOR. IN CASE OF SPILL: WIPE OR SCRAPE UP SPILLED MATERIAL MAI

NTAIN GOOD VENTILATION FOR LARGE SPILLS. PLACE SCRAP MATERIAL IN A WELL

VENTILATED PLACE AND ALLOW TO

CURE TO RUBBER. FIRST AID: INGESTION: DO NOT

INDUCE VOMITING. KEEP INDIVIDUAL CALM. OBTAIN MEDICAL ATTENTION. INHALATION:

REMOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. SKIN: WIPE OFF PASTE WITH PAPER

TOWEL OR CLOTH. WASH EXPOSED AREA WITH SOAP AND WATER. EYE: FLUSH AT LEAST 15

MINUTES WITH WATER. OB TAIN MEDICAL ATTENTION.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use

by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or

viability by or to any person or persons outside the Department of Defense

nor any person or persons contracting with any instrumentality of the United

States of America and disclaims all liability for such use. Any person

utilizing this instruction who is not a military or civilian employee

of the

United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.