

LHB INDUSTRIES -- SO-SURE CORRECTION FLUID THINNER/1074026

=====  
MSDS Safety Information  
=====

FSC: 7510  
NIIN: 01-333-6241  
MSDS Date: 07/25/1997  
MSDS Num: CGXRC  
Product ID: SO-SURE CORRECTION FLUID THINNER/1074026  
MFN: 02  
Responsible Party  
Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. L  
OUIS MO 63134  
Info Phone Number: 314-522-3141  
Emergency Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141  
Preparer's Name: MARY GANNON  
Review Ind: Y  
Published: Y

=====  
Preparer Co. when other than Responsible Party Co.  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134

=====  
Contractor Summary  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134  
Phone: 314-522-3141

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: THINNER,CORRECTION FLUID  
Specification Number: A-A-212B  
Type/Grade/Class: TYPE III  
Unit of Issue: DZ  
UI Container Qty: 0  
=====

=

Ingredients

=====  
Cas: 142-82-5  
RTECS #: MI7700000  
Name: N-HEPTANE  
% Wt: &lt;62.66  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 400 PPM  
ACGIH TLV: 400 PPM  
-----

Cas: 8052-41-3  
RTECS #: WJ8925000  
Name: STODDARD SOLVENT  
% Wt: 34.67  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 100 PPM  
ACGIH TLV: 100 PPM  
-----

Cas: 110-54-3  
RTECS #: MN9275000  
Name: HEXANE (N-HEXANE) (CERCLA)  
% Wt: &lt;6.53  
Other RE  
C Limits: NONE RECOMMENDED  
OSHA PEL: 50 PPM  
ACGIH TLV: 50 PPM  
EPA Rpt Qty: 1 LB  
DOT Rpt Qty: 1 LB  
-----

Cas: 111-65-9  
RTECS #: RG8400000  
Name: N-OCTANE  
% Wt: &lt;1.95  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 300 PPM  
ACGIH TLV: 300 PPM  
-----

Cas: 108-88-3  
RTECS #: XS5250000  
Name: TOLUENE (SARA 313) (CERCLA)  
% Wt: &lt;1.95  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 100 PPM  
ACGIH TLV: 50 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS  
-----

-----  
Cas: 110-82-7  
RTECS #: GU6300000  
Name: CYCLOHEXANE (SARA 313) (CERCLA)  
% Wt: &lt;1.95  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 300 PPM  
ACGIH TLV: 300 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS  
-----

RTECS #: 9999999VO  
Name: VOC = 714 G/L  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: NOT RELEVANT  
ACGIH TLV: NOT RELEVANT  
=====

Health Hazards Data  
=====

=====  
Route Of Entry Inds - Inhalation: YES  
Skin: YES  
Ingestion: YES  
Carcinogenicity Inds - NTP: NO  
IARC: NO  
OSHA: NO

Effects of Exposure: EYE: IRRIT. SKIN: IRRIT, DISCOMFORT. INHAL: IRRIT TO NOSE/THROAT, DIZZY, DROWSY, EUPHORIA, INCOORDINATION, DISORIENTED, HEADACHE, NAUSEA, VOMIT. INGEST: IRRIT TO MOUTH/THROAT/STOMACH, ABDOMINAL & CHES T DISCOMFORT, NAUSEA, VOMIT, DIARRHEA, WEAKNESS, ASPIRATION DURING SWALLOWING OR VOMIT RESULTING IN LUNG INFLAM/DAMAGE.

Medical Cond Aggravated

By Exposure: PRE-EXISTING SKIN DISORDERS MAY INCREASE SENSITIVITY. PRE-EXISTING LUNG DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS MATERIAL.

First Aid: EYE: FLUSH W/WATER FOR 15 MINUTES. SKIN: WASH W/SOAP & WATER. WASH CLOTHES BEFORE REUSE. INHAL: REMOVE TO FRESH AIR. ARTIF RESP/OXYGEN IF NEEDED. INGEST: DONT INDUCE VOMIT. IN ALL CASES, GET MED AID.  
=====

Handling and Disposal  
=====

Spill Release Procedures: REMOVE IGNITS. VENT AREA. PICK UP SPILLS W/ABSORBENT MATERIAL. AVOID CONTACT W/SKIN & EYES.

Waste Disposal Methods: IN ACCORDANCE W/FEDERAL, STATE AND LOCAL REGULATIONS.

Handling And Storage Precautions: KEEP AWAY FROM CHILDREN. USE W/ADEQUATE VENTILATION.

Other Precautions: DONT USE NEAR OPEN FLAME, SPARKS OR OTHER IGNITION SOURCES.

=====  
Fire and Explosion Hazard Information  
=====

=====  
Flash Point Method: TCC

Flash Point Text: 14F,-10C

Autoignition Temp Text: 399F

Lower Limits: 1.0

Upper Limits: 7.0

Extinguishing Media: DRY CHEMICAL, FOAM, CARBON DIOXIDE.

Fire Fighting Procedures: USE SCBA W/FULL-FACE PIECE & PROTECTIVE CLOTHES. USE WATER TO COOL CONTAINERS. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IT USE.

Unusual Fire/Explosion Hazard: KEEP FROM IGNITS. CLOSED CONTAINERS EXPLODE IN HIGH HEAT. DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION

PRODUCTS MAY POSE A HEALTH HAZARD.

=====  
Control Measures  
=====

Respiratory Protection: USE NIOSH/MSHA APPROVED AIR-PURIFYING OR AIR-SUPPLIED RESPIRATOR ABOVE TLV.

Ventilation: LOCAL EXHAUST PREFERRED. MECHANICAL (GENERAL) SUFFICIENT.

Protective Gloves: RECOMMENDED

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: EYEWASH STATION

Work Hygienic Practices: WASH HANDS AFTER USING PRODUCT. DONT SMOKE OR EAT WHILE USING PRODUCT.

=====  
Physical/Chemical Properties  
=====

B.P. Text: 201 TO 288F

M.P/F.P Text: NE

Decomp Text: NO DATA

Vapor Pres: 53 @ 68F

Vapor Density: 3.3 AIR =1

Spec Gravity: 0.714 WATER =1

PH: NA

Viscosity: NE

Evaporation Rate & Reference: >1 (BUAC = 1)

Solubility in Water: INSOLUBLE

Appearance and Odor: COLORLESS LIQUID, W/MILD ODOR.

Corrosion Rat

e: NE

=====  
Reactivity Data  
=====

Stability Indicator: YES

Stability Condition To Avoid: EXTREME HEAT AND IGNITION SOURCES.

Materials To Avoid: STRONG ACIDS OR BASES, OXIDIZING AGENTS.

Hazardous Decomposition Products: TOXIC LEVELS OF CARBON MONOXIDE, CARBON DIOXIDE, IRRITATING ALDEHYDES & KETONES.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: EXTREME TEMPERATURES

=====  
Toxicological Information  
=====

=====  
Ecological Information  
=====

=====  
MSDS Transport Information  
=====

=====  
Regulatory Information  
=====

=====  
Other Information  
=====

=====  
Transportation Information  
=====

Responsible Party Cage: 0FTT5

Trans ID NO: 126347

Product ID: SO-SURE CORRECTION FLUID THINNER/1074026

MSDS Prepared Date: 07/25/1997

Review Date: 04/29/1998

MFN: 2

Multiple KIT N

umber: 0

Review IND: Y

Unit Of Issue: DZ

Container QTY: 0

=====  
Detail DOT Information  
=====

DOT PSN Code: HAD

DOT Proper Shipping Name: HEPTANES

Hazard Class: 3

UN ID Num: UN1206

DOT Packaging Group: II

Label: FLAMMABLE LIQUID

Special Provision: T2

Packaging Exception: 150

Non Bulk Pack: 202

Bulk Pack: 242

Max Qty Pass: 5 L

Max Qty Cargo: 60 L

Vessel Stow Req: B  
=====

=====  
Detail IMO Information  
=====

IMO PSN Code: NDD  
IMO Proper Shipping Name: ROCKETS, LINE THROWING  
IMDG Page Number: 1293  
UN Number: 0240  
UN Hazard Class: 1.3 G  
IMO Packaging Group: -  
Subsidiary Risk Label: -  
EMS Number: 1-03  
MED First Aid Guide NUM: \*

=====  
Detail IATA Information  
=====

IATA PSN Code: NDD  
IATA UN ID Num: 1206  
  
IATA Proper Shipping Name: HEPTANES  
IATA UN Class: 3  
IATA Label: FLAMMABLE LIQUID  
UN Packing Group: II  
Packing Note Passenger: 305  
Max Quant Pass: 5L  
Max Quant Cargo: 60L  
Packaging Note Cargo: 307

=====  
Detail AFI Information  
=====

AFI PSN Code: XXX  
=====

HAZCOM Label  
=====

Product ID: SO-SURE CO  
RRECTION FLUID THINNER/1074026  
Cage: 0FTT5  
Company Name: LHB INDUSTRIES  
Street: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO  
Zipcode: 63134  
Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141  
Label Required IND: Y  
Date Of Label Review: 10/12/1999  
Status Code: A  
Origination Code: G  
Hazard And Precautions: EYE: IRRIT. SKIN: IRRIT, DISCOMFORT. INHAL: IRRIT TO  
NOSE/THROAT, DIZZY, DROWSY, EUPHORIA, INCOORDINATION, DISORIENTED, HEADACHE,  
NAUSEA, VOMIT. INGEST: IRRIT TO MOUTH/THROAT/STOMACH, ABD

OMINAL & CHES T

DISCOMFORT, NAUSEA, VOMIT, DIARRHEA, WEAKNESS, ASPIRATION DURING SWALLOWING OR VOMIT RESULTING IN LUNG INFLAM/DAMAGE.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.