View NSN Online: https://aerobasegroup.com/nsn/8010-01-344-5322

NILES CHEMICAL PAINT CO. -- N-5113 WHITE SI ALKYD -- 8010-01-344-5322

Product ID:N-5113 WHITE SI ALKYD MSDS Date:05/01/1997 FSC:8010 NIIN:01-344-5322 MSDS Number: CGXSM === Responsible Party === Company Name: NILES CHEMICAL PAINT CO. Address:225 FORT STREET Box:307 City:NILES State:MI ZIP:49120 Country:US Info Phone Num:616-683-3377 Emergency Phone Num:219-236-58 56 Preparer's Name: MICHEAL LICHATOWICH CAGE:02388 === Contractor Identification === Company Name: NILES CHEMICAL PAINT Address:225 FORT STREET Box:307 City:NILES State:MI ZIP:49120 Country:US Phone:616-683-3377/219-236-5856 CAGE:02388

Ingred Name:CALCIUM CARBONATE CAS:1317-65-3 RTECS #:EV9580000 Fraction by Wt: 27.0% Other REC Limits:NONE RECOMMENDED

Ingred Name:HIGH SOLIDS SILICONE (VP = 1.5 @ 20C) Fraction by Wt: 25.0% Othe r REC Limits:NONE RECOMMENDED

Ingred Name:MINERAL SPIRITS (VP = .0 @ 20C) CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 16.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 PPM ACGIH TLV:100 PPM

Ingred Name:#100 SOLVENT (VP = 4.4 @ 20C) CAS:64742-95-6 Fraction by Wt: 6.0% Other REC Limits:NONE RECOMMENDED

Ingred Name:ZINC OXIDE (SARA 313) (CERCLA) CAS:1314-13-2 RTECS #:ZH4810000 Fraction by Wt: 3.0% Other REC Limits:NONE RECOMMENDED

Ingred Name:COBALT COMPOUNDS (AS CO) (SARA 313) CAS:7440-48-4 RTECS #:GF8750000 Fraction by Wt: AIR Spec Gravity:1.434 pH:NA VOC Grams/Liter:2.8 Viscosity:100 KU MAX. Evaporation Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:YES Appearance and Odor:LIQUID, ODOR OF SOLVENT. Percent Volatiles by Volume:41.43 Corrosion Rate:MINIMAL

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Stability Condition to Avoid:HIGH TEMPERATURES. Hazardous Decomposition Products:CA

N PRODUCE CARBON MONOXIDE AND CARBON DIOXIDE.

Waste Disposal Methods: IN ACCORDANCE W/FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or impli

ed, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.