View NSN Online: https://aerobasegroup.jp/nsn/6850-01-454-6489

Product ID:PREP RITE MSDS Date:05/28/1998 FSC:6850 NIIN:01-454-6489 Status Code:A **MSDS Number: CHWCR** === Responsible Party === Company Name: ECOLINK INC Address:1481 ROCK MOUNTAIN BLVD **City:STONE MOUNTAIN** State:GA ZIP:30083 Country:US Info Phone Num: (800) 886-8240 OR 404-621-8240 Emergency Phone Num: (800) 886-8240 OR 40 4-621-8240 CAGE:0WU71 === Contractor Identification === Company Name: ECOLINK INC Address:1481 ROCK MOUNTAIN BLVD Box:City:STONE MOUNTAIN State:GA ZIP:30083-1505 Country:US Phone:800-886-8240/770-621-8240 CAGE:0WU71

Ingred Name:N-METHYLPYRROLIDONE CAS:872-50-4 RTECS #:UY5790000 Fraction by Wt: 91% Other REC Limits:NONE RECOMMENDED

Ingred Name:TRIETHANOLAMINE CAS:102-71-6 RTECS #:KL9275000 Fraction by Wt: 5-8% Other REC Limits LD50 LC50 Mixture:ORAL LD50 (RAT) IS Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES-VAPORS SLIGHTLY UNCOMFORTABLE, SPLASHING IRRITATING. SKIN-WILL CAUSE SEVERE DERMATITIS ON REPEATED PROLONGED CONTACT. Explanation of Carcinogenicity:NOT CARCINOGENIC. Effects of Overexposure:INHALATION-PALLOR, NAUSEA, L ACK OF COORDINATION, STUPOR. EYES-WILL CAUSE PAINFUL BURNING OR STINGING OF EYES AND LIDS, WATERING EYES AND INFLAMMATION OF CONJUNCTIVIA. SKIN-BLISTERS, CRACKING, EDEMA, R EDNESS.

Medical Cond Aggravated by Exposure:NONE KNOWN.

First Aid:EYE-FLUSH EYES WITH WATER FOR AT LEAST 15 MIN. CONSULT A PHYSICIAN. SKIN CONTACT-WASH AFFECTED AREA WELL WITH SOAP AND WATER. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

INHALATION-REMOVE TO AN UNCON TAMINATED AREA, ADMINISTER OXYGEN IF NECESSARY. IF VICTIM HAS STOPPED BREATHING, BEGIN CPR. GET MEDICAL ATTENTION. INGESTED-IF CONSCIOUS, GIVE WATER BUT DO NOT INDUCE VOMITING. GET IMMEDIATE MED. AID.

Flash Point Method:TCC

Flash Point:>200F,>93C

Extinguishing Media:WATER SPRAY, ALCOHOL FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

Fire Fighting Procedures: FIREFIGHTERS SHOULD WEAR PO SITIVE PRESSURE.

SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID. DANGEROUS FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME.

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION! ABSORB LIQUID WITH EARTH, SAND OR SIMILAR INERT MATERIAL AND DISPOSE OF WITH SOLID WASTE ACCORDING TO LOCAL, STATE AND FEDERAL REG ULATIONS. FLUSH SPILL AREA WITH WATER. Neutralizing Agent:NONE

======================================
Handling and Storage Precautions: KEEP CONTAINER AND VAPORS AWAY FROM HEAT AND FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE. Other Precautions: AVOID CONTACT WITH EYES AND SKIN.
========= Exposure Controls/Personal Protection ====================================
Respiratory Protection:NONE REQUIRED UNDER NORMAL USE CONDITIONS. Ventilation:LOCAL EXHAUST/HOOD OR FAN MAY BE U SED. SET TO MAINTAIN BELOW TLV. MECHANICAL/NONE REQUIRED. Protective Gloves:IMPERVIOUS GLOVES ARE RECOMMENDED. Eye Protection:CHEMICAL GOGGLES ARE RECOMMENDED. Other Protective Equipment:NONE NORMALLY REQUIRED.Y SHOWER. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING MIST OR VAPOR. USE WITH ADEQUATE VENTILATION. Supplemental Safety and Health WASH EQUIPMENT WITH STEAM OR WARM WATER UNTIL CLEAN.
======================================
HCC:N1 Bailing Bt/B D. Tayt: 2005 02C

F Boiling Pt:B.P. Text:200F,93C Melt/Freeze Pt:M.P/F.P Text:-4F,-20C Vapor Pres:3.0 Spec Gravity:1.03 Evaporation Rate & amp; Reference: