View NSN Online: https://aerobasegroup.com/nsn/6850-00-973-9091

CASTOLEUM CORP -- TRIZOL CREEP -- 6850-00-973-9091

============= Product Identification =============

Product ID:TRIZOL CREEP MSDS Date:01/01/1997

FSC:6850

NIIN:00-973-9091 Status Code:A

MSDS Number: CHWRB === Responsible Party ===

Company Name: CASTOLEUM CORP

Address:31 FULLERTON AVE

Box:41

City:YONKERS

State:NY ZIP:10710 Country:US

Info Phone Num:914-664-5877 FAX 914-664-9383

Emergency Phone Num:914-664-5877

CA

GE:66662

=== Contractor Identification ===

Company Name: CASTOLEUM CORP THE

Address:240 E 7TH ST Box:City:MOUNT VERNON

State:NY

ZIP:10550-4615 Country:US

Phone:914-664-5877

CAGE:66662

======= Composition/Information on Ingredients ========

Ingred Name:TRIETHANOLAMINE

CAS:102-71-6

RTECS #:KL9275000 Fraction by Wt: 2-5%

Other REC Limits: NONE RECOMMENDED

Ingred Name:DIETHANOLAMINE (SARA 313) (CERCLA)

CAS:111-42-2

RTECS #:KL2975000 Fraction by Wt: 1-4%

Other REC Limits: NONE RECOMMENDE

D

OSHA PEL:3 PPM ACGIH TLV:3 PPM EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: POLYALKYLENE GLYCOL

Fraction by Wt: 6-12%

Other REC Limits: NONE RECOMMENDED

Ingred Name: DIETHYLENE GLYCOL MONOETHYL ETHER

CAS:111-90-0

RTECS #:KK8750000 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

Ingred Name: ETHYLENE GLYCOL (SARA 313) (CERCLA)

CAS:107-21-1

RTECS #:KW2975000 Fraction by Wt: .5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:50 PPM

ACGIH TLV:50 PPM, VAPOR

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ing

red Name: NONYLPHENOL ETHOXYLATE

CAS:26027-38-3 RTECS #:MD0906000 Fraction by Wt: 1-6%

Other REC Limits: NONE RECOMMENDED

========== Hazards Identification ==============

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Explanation of Carcinogenicity:NO

First Aid:SKIN: WASH WITH SOAP AND WARM WATER. INHALE: REMOVE TO FRESH

AIR. EYES: FLUSH THO

ROUGHLY WITH MUCH WATER FOR SEVERAL MINUTES; GET MED AID.
======================================
Flash Point:NONE TO BOILING
========= Accidental Release Measures ==========
Spill Release Procedures:ABSORB ON CLAY OR OTHER SUITABLE MATERIAL AND SWEEP UP.
====== Exposure Controls/Personal Protection ========
Ventilation:NORMAL LOCAL EXHAUST AND MECHANICAL VENTILATION. Protective Gloves:RECOMMENDED Eye Protection:SAFETY G OGGLES/FACE SHIELD Work Hygienic Practices:WASH HANDS AND EXPOSED SKIN AFTER CONTACT. LAUNDER CONTAM CLOTHING BEFORE REUSE. Supplemental Safety and Health NK
========= Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:212F,100C Spec Gravity:1.01 Solubility in Water:COMPLETE Appearance and Odor:SKY BLUE LIQUID WITH PLEASANT ODOR
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES OXIDIZING OR ACIDIC M ATERIALS
======== Disposal Considerations ===========
Waste Disposal Methods: AS LOCAL LAWS PERMIT.
Disclaimer (provided with this information by the compiling agencies):

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent

professional advice to verify and assume responsibility for the suitability of this information to their particular situation.