

SHERWIN-WILLIAMS CO -- 3.5 VOC LEAD/CHROME FREE EPOXY POLY-PRIMER (A), P&L 724736 --
8010-01-309-0329

=====
Product Identification
=====

Product ID:3.5 VOC LEAD/CHROME FREE EPOXY POLY-PRIMER (A), P&L 724736

MSDS Date:09/23/1997

FSC:8010

NIIN:01-309-0329

Kit Part:Y

MSDS Number: CHWRP

=== Responsible Party ===

Company Name:SHERWIN-WILLIAMS CO

Address:101 PROSPECT AVE N W

City:CLEVELAND

State:OH

ZIP

:44115-1042

Country:US

Info Phone Num:216-566-2902

Emergency Phone Num:216-566-2917

CAGE:54636

=== Contractor Identification ===

Company Name:SHERWIN-WILLIAMS CO THE

Address:101 PROSPECT AVE NW

Box:City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Phone:800-251-2486/216-566-2242

CAGE:54636

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA 313) (CERCLA)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 4%

Other REC Limits:OSHA STEL 150PPM SKN

OSHA PEL:1

00PPM (SKIN)
ACGIH TLV:S, 50 PPM; 9495
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL PROPYL KETONE (2-PENTANONE)
CAS:107-87-9
RTECS #:SA7875000
Fraction by Wt: 16%
Other REC Limits:OSHA STEL 250PPM
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/250STEL;9495

Ingred Name:EPOXY POLYMER
Fraction by Wt: 13%
Other REC Limits:N/KE RECOMMENDED
OSHA PEL:N/K ESTABLISHED
ACGIH TLV:N/K ESTABLISHED

Ingred Name:SILICA, CRYSTALLINE - QUARTZ
CAS:14808-60-7
RTECS #:VV7330000
Fraction by Wt: 18%
Other REC
Limits:NONE RECOMMENDED
OSHA PEL:.1MB/M3 RESP. DUST
ACGIH TLV:0.1 MG/M3 RDUST;9495

Ingred Name:TALC (CONTAINING ASBESTOS)
CAS:14807-96-6
RTECS #:MW2700000
Fraction by Wt: 4%
Other REC Limits:N/KE RECOMMENDED
OSHA PEL:2MB/M3 RDUST
ACGIH TLV:2MG/MC RDUST

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 30%
Other REC Limits:N/KE RECOMMENDED
OSHA PEL:10(5)MG/M3 (DUST)
ACGIH TLV:10 MG/M3 TDUST; 9495

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INHALATION, HEADACHE, DIZZINESS,
NAUSEA, LOSS OF CO-ORD IRRITATION. EYES: REDNESS, ITCHING,
IRRITATION, BURNING SENSATION. SKIN: IRRITATION, ITCHING BURNING
SENSATION, REDNESS, POSSIBLE ALERGIC SKIN REACTION
Explanation of Carcinogenicity:CHRISTALINE SILICA (QUARTZ,
CHRISTOBALITE)
Effects of Overexposure:POSSIBLE NERV SYSTM DEPRESSI
ON,
UNCONSCIOUSNESS, POSSIBLY DEATH. SOLVENTS: POS BRAIN AND NERV
SYSTM DAMAGE, POS EFFECTS TO LIVER, URINARY, CARDIOVASC AND REPROD
SYSTEM
Medical Cond Aggravated by Exposure:SKIN ALLERGIES OR OTHER SKIN
CONDNTS

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING, KEEP
WARM AND QUIET. SKIN: WASH THOROUGHLY W/SOAP & WTR.REMOV CONTAM
CLOTHING, LAUNDER BEFORE RE-USE. EYES: FLUSH W/LRG AMOU
NTS OF WTR
15 MIN, G ET MED AID. INGESTION: GET MED AID.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:44.0F,6.7C
Autoignition Temp:Autoignition Temp Text:846F
Lower Limits:1
Upper Limits:8.7
Extinguishing Media:CO2, DRY CHEM, FOAM
Fire Fighting Procedures:FULL-PROTECT EQIPT, INCL. SCUBBA, WTR SPRAY
MAY BE INEFFECTIVE. IF WTR IS USED, FOG NOZZLES PREF. WTR USED TO
COOL CLOSED CNTNRS TO PREVENT EXPLOSION
Unusual Fire/Explo
sion Hazard:KEEP CNTNRS TIGHTLY CLOSED. ISOLATE FROM
ALL HEAT & IGNITABLES. CLOSED CNTNRS MAY EXPL WHEN EXPOSED TO EXTRM
HEAT. IN EMERG, OVEREXPSR TO DECOMP PRODS*

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, VELTILATE AND
REMOVE W/INERT ABSORBANT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:CONTNTS FLAMABLE, KEEP AWAY FROM
HEAT/IGNITABLES.

KEEP VENTED. DO NOT SMOKE,CONSULT NFPA CODE. USE
APRVD BNDG/GRDG, KEEP CLOSED WHEN NOT IN USE.
Other Precautions:USE ONLY COMPLETE AND PRROPRIATE LABELING. DO NOT
TAKE INTERNALLY, KEEP OUT OF REACH OF CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR PROPERLY FITTED ORGANIC VAPOR/PARTICULATE
RESPIRATOR APRVD BY NIOSH/MSHA, WHEN SANDING,ABRADING, WEAR
MIST/DUST RESPIRATOR APROVD BY NIOSH/MSHA

Ventilation:LOCAL EXHAUST PREF

, GENERAL EXHAUST ACCEPTABLE IF EXPOSURE

BELO EXPSUR LMTS, USE ENOUGH VENT AVOID MST CNTNING PR TIC

Protective Gloves:AS RECOM BY GLOVE SUPPLIER

Eye Protection:SAFETY SPECS W/ UNPERF SIDE-SHIELDS

Other Protective Equipment:BARRIER CREAM

Supplemental Safety and Health

MUST BE MXD W/OTHER COMPONENTS BEFORE USE. READ AND FOLLOW DIRECTIONS
BEFORE OPENING PACAGES OF ANY COMPONENTS. INTENT MIS-USE, HARMFUL
OR FATAL. * MAY CAUSE HLTH HZARD, SYMPRMS MAY BE DELAYED. GET
MED AID

=====

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:217F,103C

Vapor Pres:19.2@25C

Spec Gravity:1.58

VOC Grams/Liter:2.87

Viscosity:NONE

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:LIQUID, W/SOLVENT ODOR

Percent Volatiles by Volume:42%

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO2 CO

=====
===== Disposal Considerations =====

=====

Waste Disposal Methods:WASTE MAY BE HZRDOUS, MUST BE TESTED FOR
IGNITABILITY. INSINORATE IN APRVD FACILITY.DO NOT INSINORATE CLOSD
CNTNR. DISPOSEOF PER FED STE AND LOCAL REGS RE: POLUTION

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
exp
ressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.