

GIBSON-HOMANS CO -- BLACK JACK ALL WEATHER RF CMT -- 5610-00-236-4964

===== Product Identification =====

Product ID:BLACK JACK ALL WEATHER RF CMT

MSDS Date:10/12/1990

FSC:5610

NIIN:00-236-4964

Status Code:A

MSDS Number: CHXQB

=== Responsible Party ===

Company Name:GIBSON-HOMANS CO

Address:1755 ENTERPRISE PARKWAY

City:TWINSBURG

State:OH

ZIP:44087

Country:US

Info Phone Num:216-467-8128

Emergency Phone Num:216-425-3255

CAGE:GIBHO

=== Contractor Identification ===

Company Name:GIBBSON-HOMANS CO

Address:1755 ENTERPRISE PARKWAY

Box:City:TWINSBURG

State:OH

ZIP:44087

Country:US

Phone:216-467-8128

CAGE:0U534

Company Name:GIBSON-HOMANS CO

Address:1755 ENTERPRISE PARKWAY

City:TWINSBURG

State:OH

ZIP:44087

Country:US

Phone:216-425-3255

CAGE:GIBHO

===== Composition/Information on Ingredients =====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 10-30%

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

===== Hazard

s Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: SKIN: PROLONGED/REPEATED

CONTACT MAY CAUSE IRRITATION. EYES: MAY CAUSE IRRITATION, BLURRED

VISION. INHALATION: EXCESSIVE BREATHING OF HIGH VAPOR

CONCENTRATIONS CAN CAUSE NASAL AND RESPIRATORY I RRI TATION,

DIZZINESS, NAUSEA, POSSIBLE UNCONSCIOU

SNES AND EVEN ASPHYXIATION.

INGESTION: CAN CAUSE (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ: GASTROINTESTINAL IRRITATION, NAUSEA,

VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE

CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

Medical Cond Aggravated by Exposure:PRE-EXISTING LUNG AND SKIN

DISORDERS.

===== First Aid Measures =====

First Aid:SKIN: WASH WITH SOAP AND WATER. EYES:

FLUSH WITH LARGE

AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. INHALATION: REMOVE PERSON

FROM AFFECTED AREA. IF BREATHING IS DIFFICULT ADMINISTER OXYGEN. IF

BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. INGESTION: DO

NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:105F,41C

Lower Limits:0.8%

Upper Limits:7.0%

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICALS

Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT . WATER MAY CAUSE FROTHING, APPLY CAUTIOUSLY.

Unusual Fire/Explosion Hazard:KEEP AWAY FROM SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE SPILL AREA. RECOVER FREE LIQUID, ADD
ABSORBENT TO SPILL AREA. REMOVE SOURCES OF IGNITION. VENTILATE AREA
IF NECESSARY.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Han

ding and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM SOURCES OF IGNITION.
USE ONLY WITH ADEQUATE VENTILATION. AVOID PROLONGED/REPEATED
CONTACT WITH SKIN.

Other Precautions:KEEP OUT OF THE REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NEEDED IN WELL VENTILATED AREA. IF
TLV IS EXCEEDED, A NIOSH APPROVED BREATHING APPARATUS IS
RECOMMENDED.

Ventilation:AS NECESSARY TO
MAINTAIN EXPOSURE BELOW TLV LEVEL.

Protective Gloves:OIL RESISTANT GLOVES.

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective Equipment:ANSI APPRVD EYE WASH & DELUGE SHOWER . AS
NECESSARY.

Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING, LAUNDER BEFORE
REUSE.

Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres:21 @ 25C

Vapor Density:>1

Spec Gr

avity:1.1

Evaporation Rate & Reference: