

FARWEST PAINT MFG CO -- BLACK TRAFFIC LINE PAINT, TYPE 1, #37038 1073(A-A-2886) --  
8010-00-286-9072

=====  
Product Identification  
=====

Product ID:BLACK TRAFFIC LINE PAINT, TYPE 1, #37038 1073(A-A-2886)

MSDS Date:07/01/1997

FSC:8010

NIIN:00-286-9072

Status Code:A

MSDS Number: CJFXL

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP

:98168-3251

Country:US

Emergency Phone Num:206-244-8844

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL SPIRITS 350

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 2.5%

OSHA PEL:100PPM

ACGIH TLV:100PPM

Ingred Name:MINERAL SPIRITS 250

CAS:64742-89-8

Fraction by W

t: 21.6%  
OSHA PEL:250PPM  
ACGIH TLV:250PPM

Ingred Name:TOLUENE  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 4.9%  
OSHA PEL:100PPM  
ACGIH TLV:100PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Effects of Overexposure:SKIN: THIS MATERIAL MAY CAUSE IRRITATION,  
SENSITIZATION, OR DEFATTING UPON PROLONGED OR REPEATED CONTACT.  
INHALATION:EXCESSIVE EXPOSURE TO VAPORS OR S  
PRAY MIST MAY RESULT IN  
HEADACHES, DIZZINESS, NAUS EA OR LOSS OF CONSCIOUSNESS. SOME  
REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED AND OCCUPATIONAL  
OVEREXPOSURE TO SULVANTS, WITH PERMANENT BRAIN AND NERVOUS SYSTEM  
DAMAGE. EYES: MAY BE AN EYE IRRITANT .  
Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE WITH  
SAFE HANDLING INSTRUCTIONS.

=====  
===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH WITH SOAP AND WATER. REMOV  
E ANY  
CONTAMINATED CLOTHING BEFORE REUSE. EYES: FLUSH WITH LARGE AMOUNTS  
OF WATER FOR 15 MINUTES. GET MEDUCAL ATTENTION. INGESTION: DRINK  
WATER. DO NOT INDUCE VOMITING. KEEP PERSON WARM AND QUIET. CALL  
DR. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL  
PNEUMONITIS, WHICH CAN BE FATAL. INHALATION: REMOVE TO FRESH AIR.  
IF RESPIRATORY SYMPTOMS DEVELOP, SEEK MEDICAL ATTENTION AT ONCE.

=====  
===== Fire Fighting Measures =====

Flash Po

int Method:TCC

Flash Point:=7.2C, 45.F

Lower Limits:0.7%

Extinguishing Media:FOAM, CO2, OR DRY CHEMICAL, OR WATER FOG. USE THESE OR ANY CLASS B EXTINGUISHING AGENT. WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIUM, BUT HELPFUL IN KEEPING ADJACENT CONT COOL

Fire Fighting Procedures:FIRE FIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR SELF-CONTAINED BREATHING APARATUS. EVACUATE AREA OF UNPROTECTED PERSONEL. WEAR PROTECTIVE CLOTHING.

Unusual Fi

re/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHTS. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. ABSORB MATERIAL WITH AN ABSORBANT MATERIAL SUCH AS SAW DUST, VERMICULITE, OR SAND, AND PLACE MATERIAL INTO A CLOSED CONTAINER. IF LARGE SPILL, DYKE ARE A TO PREVENT MAT ERIAL FROM ENTERING WATER SUPPLY OR SEWERS. WEAR PROTECTIVE EQUIPMENT DURING CLEAN UP.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED/REPEATED INHALATION OF HEATED VAPORS & SPRAY MIST. KEEP AWAY FROM HEAT/OPEN FLAME. MATERIAL MAY CAUSE SENSITIZATION. DO NOT GET IN EYES, ON SKIN, OR CLOTHING. DO NOT ALLOW CONTAM. CLO THING TO CONTACT SKIN. DO NOT WELD ON FULL OR EMPTY CONT. KEEP CONT. CLOSED WHEN NOT IN USE.

Other Precautions:KEEP PROPERLY LABELED IN ACCORDANCE WITH STATE, LOCAL, AND FEDERAL REGULATIONS. FOR MORE INFO, CONTACT YOUR LOCAL OR STATE AGENCY, OR FEDERAL EPA AT: 800-424-9346, OR 202-382-3000.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CANISTER-TYPE RESPIRATOR MUST BE WORN TO PREVENT INHALATION OF VAPOR OR SPRAY MIST WHEN TLV OR PEL IS EXCEEDED.

Ventilation:GENERAL VENTILATION IS REQUIRED DURING NORMAL USE. LOCAL VENTILA

TION REQUIRED DURING CERTAIN OPERATIONS TO KEEP EXPOSURE  
LIMITS BELOW THE LEVEL LISTED IN SEC 11

Protective Gloves:CHEM RESISTANT NITRILE, NEOPRENE, OR RUBBER GLOVES

Eye Protection:FACE SHIELD OR CHEM GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN  
CONTACT. EYE WASH STATION AND SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

=====

Vapor Pres:53MMHG@20C

Vapor Density:>AIR

VOC Pounds/Gallon:352

Evaporation Rate & Reference: