

PRAXAIR SURFACE TECHNOLOGIES INC -- NI-114, WELDING POWDER -- 3439-01-426-3164
===== Product Identification =====

Product ID:NI-114, WELDING POWDER
MSDS Date:06/22/1994
FSC:3439
NIIN:01-426-3164
Status Code:A
MSDS Number: CJQGW
=== Responsible Party ===
Company Name:PRAXAIR SURFACE TECHNOLOGIES INC
Address:1555 MAIN STREET
City:INDIANAPOLIS
State:IN
ZIP:46224-3283
Country:US
Info Phone Num:317-240
-2650
Emergency Phone Num:317-240-2209
Resp. Party Other MSDS Num.:PRODUCT CODE:036014-04
Preparer's Name:MICHELLE ALEXANDER
Chemtrec Ind/Phone:(800)424-9300
CAGE:0FGH2
=== Contractor Identification ===
Company Name:PRAXAIR SURFACE TECHNOLOGIES INC
Address:1555 MAIN STREET
Box:City:INDIANAPOLIS
State:IN
ZIP:46224-3283
Country:US
Phone:317-240-2650
CAGE:0FGH2
Company Name:STARGHILL TECHNOLOGIES CORP
Address:3850 OAKMAN BLVD
Box:City:DETROIT
State:MI
ZIP:48204-1119
Country:US
Phone:313-933-4141
Co

ntract Num:SP0490-95-D-4037
CAGE:0VYG8

===== Composition/Information on Ingredients =====

Ingred Name:NICKEL
CAS:7440-02-0
RTECS #:QR5950000
Minumum % Wt:50.
Maxumum % Wt:75.
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3

Ingred Name:CARBON
CAS:7440-44-0
RTECS #:FF5250000
Minumum % Wt:20.
Maxumum % Wt:50.
OSHA PEL:10 MG/M3
ACGIH TLV:2.5 MG/M3

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcino

genicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:ACUTE: EYES: MAY CAUSE IRRITATION.

SKIN CONTACT:MAY CAUSE ALLERGIC DERMATITIS, PAPULAR FORMATION,
ULCERS, DRY AND SCALY SKIN, FEVER. SKIN ABSORPTION: NO EVIDENCE OF
ADVERSE EFFECTS. INHALATION: MAY CAUSE RESPIRATORY TRACT
IRRITATION, WITH CHEST PAIN, VOMITNG, DIARRHEA, BURNING SENSATION,
AND CENTRAL NERVOUS SYSTEM DEPRESSION. MAY ALSO CAUSE INTERSTITIAL
PNEUMONITIS AND SENSITIZATION OF THE RESPIRA T

ORY TRACT. INGESTION:

MAY CAUSE NAUSEA, ABDOMINAL PAIN, VOMITING, DIARRHEA, CENTRAL
NERVOUS SYSTEM DEPRESSION, AND BURNING SENSATION. CHRONIC: EYES:
DAMAGE. SKIN: AFFECT WHOLE BODY WITH LESIONS, SORE NESS, ITCHING.
INHALATION: EMPHYSEMA.

Explanation of Carcinogenicity:NICKEL HAS BEEN DETERMINED TO CAUSE
CANCER IN EXPERMENTAL ANIMALS (IARC, NTP). NICKEL IS LISTED AS A
PROBABLE HUMAN CARCINOGEN.

Effects of Overexposure:EYES: IRRITATION, REDNESS, EXCESS REDNESS OF
CONJUN

CTIVA, CORNEAL DAMAGE. SKIN: DERMATITIS, REDNESS, PAPULAR FORMATION, ULCERS, DRY AND SCALY SKIN, FEVER. INHALATION: RESPIRATORY TRACT IRRITATION, CHE ST PAIN, DIARRHEA, BURNING SENSATION, CNS DEPRESSION, INTERSTITIAL PNEUMONITIS, EMPHYSEMA, SENSITIZATION OF RESPIRATORY TRACT. INGESTION: NAUSEA, ABDOMINAL PAIN, VOMITING, DIARRHEA, CENTRAL NERVOUS SY STEM DEPRESSION, BURNING SENSATION.CHRONIC ECZEMA/NEURODERMATIS FROM NICKEL DOES REQUIRE CONTINUOUS METAL CONTACT.

Medica

I Cond Aggravated by Exposure:BREATHING OF DUST MAY AGGRAVATE ASTHMA AND INFLAMMATORY OR FIBROTIC PULMONARY DISEASE. MAY ALSO AGGRAVATE AN EXISTING DERMATITIS.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH PENTY OF WATER. IF DISCOMFORT PERSISTS, GET MEDICAL ATTENTION, PREFERABLY AN OPTALMOLOGIST. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. OXYGEN MAY BE GIVEN IF NECESSARY. CALL A PHYSICIAN. INGESTION: GIVE AT LEAST 2 GLASSES OF MILK OR WATER. INDUCE VOMITING, UNLESS PATIENT IS UNCONSCIOUS. CALL A PHYSICIA N. NOTES TO PHYSICIAN: THE HAZARDS OF THIS MATERIAL ARE MAINLY DUE TO ITS SENSITIZING AND MILD IRRITATING PROPERTIES. THERE IS NO SPECIFIC ANTIDOTE.

===== Fire Fighting Measures =====

Flash Point:NONE

Upper Limits:0.00%

Extinguishing Media:USE DRY POWDER METAL EXTINGUISHING MATERI
AL TO

EXTINGUISH METAL FIRES. USE APPROPRIATE EXTINGUISHER TO EXTINGUISH MATERIALS THAT MAY BE IGNITED BY THE THERMAL SPRAY FLAME.

Fire Fighting Procedures:COMPLY WITH ANSI Z49.1 SAFETY IN WELDING AND CUTTING, NFPA51B STANDARD FOR FIRE PREVENTION IN USE OF CUTTING AND WELDING PROCESSES. NFPA51 OXYGEN-FUEL GAS SYSTEMS FOR WELDING AND CUTTING, AND NFPA58 S TANDARD FOR THE STORAGE AND HANDLING OFLIQUIDIFIED PETROLEUM GASES.

Unusual Fire/Explosion Hazard:AIRBORNE DUST PARTIC

LES, ESPECIALLY METAL

DUST, AND ACCUMULATION OF SUCH SHOULD BE TREATED AS EXPLOSIVES. TO MINIMIZE DANGER FROM DUST EXPLOSIONS, ADEQUATE VENTILATION SHOULD BE PROVIDED TO SPARY BOOT H IN ACCORDANCE WITH AMERICAN WELDING SOCIETY PUBLICATION AWS2.1-73, AND ACGIH PUBLICATION "INDUSTRIAL VENTILATION".

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT TO PROTECT AGAINST HAZARDS AND DISPOSE OF PER WASTE DISPOSAL METHOD.

===== Handling and Storage =====

Handling and Storage Precautions:CAUTION: WHEN THERMAL SPRAYING; ELECTRICITY CAN CAUSE FATAL SHOCK. ARC RAYS CAN BURN EYES AND SKIN. WEAR RECOMMENDED EYE AND BODY PROTECTION. FUMES, GAS, AND DUST CAN HARM YOUR HEALTH. PROVIDE ENOUGH VENTILATION AND WEAR RESPIRATOR. Other Precautions:ALWAYS SPRAY WITH ENOUGH VENTILATION. SPARKS DURING SPRAYING CAN BE A SOURCE OF IGNITION OF COMBUSTIBLE MATERIALS.

PREVENT FIRES. REFER TO NFPA 51B "CUTTING AND WELDING PROCESSES".

===== Exposure Controls/Personal Protection =====

Respiratory Protection:DEPENDS UPON SPECIFIC USE, CONDITION, AND LOCATION. IF THERE IS DUSTINESS, WEAR RESPIRATOR SELECTED PER OSHA 1910.134, AND OSHA 29 CFR 1910.252 AND ANSI Z49.1.

Ventilation:LOCAL DUST PICK UP AND VENTILATION RECOMMENDED.

Protective Gloves:NOT REQUIRED.

Eye Protection:WHEN DUSTY USE GOGGLES PER OSHA 1910.13.

Other Protective Equip

ment:SEE ANSI Z49.1, ANSI Z87.1, ANSI Z88.2 FOR HELMETS, FACE SHIELDS AND GOGGLES.

Work Hygienic Practices:NONE PROVIDED BY MFR.

Supplemental Safety and Health
NONE PROVIDED BY MFR.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NONE

Spec Gravity:1.4 (WATER = 1)

Evaporation Rate & Reference:NON VOLATILE

Appearance and Odor:DUSTY YELLOW GRAY POWDER.

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid: YES
NONE KNOWN.

Stability Condition to Avoid: NONE KNOWN.

Hazardous Decomposition Products: WHEN THERMAL SPRAYING, DECOMPOSITION
PRODUCTS VARY WITH CONDITIONS. DECOMPOSITION PRODUCTS OF NORMAL
OPERATION FROM THIS SPRAY POWDER INCLUDE OXIDES, SUB-OXIDES,
COMPLEX OXIDES OF THE POWDERED METALS.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods: DI
SPOSE OF WASTE PER LOCAL, STATE, AND FEDERAL
REGULATIONS.

===== MSDS Transport Information =====

Transport Information: NOT REGULATED. PER MSDS: SHIPPING NAME: METAL
ALLOY POWDER NOI ITEM 136500 SUB 1. NO UN NUMBER.

===== Regulatory Information =====

SARA Title III Information: SECTION 313: THIS PRODUCT CONTAINS THE
FOLLOWING TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF
SECTION 313 OF THE EMERGENCY PL
ANNING AND COMMUNITY RIGHT TO KNOW
ACT OF 1986 AND OF CFR 372: CAS # 7440-02-0 , NICKEL,