Product ID:B44V20 HEAVY DUTY POLYURETHANE VARNISH

MSDS Date:01/01/1991

FSC:8010

NIIN:00-604-2014 Status Code:A

MSDS Number: CKDGD === Responsible Party ===

Company Name: SHERWIN WILLIAMS CO.

Address:101 PROSPECT AVE N.W.

City:CLEVLAND

State:OH ZIP:44115 Country:US

Info Phone Num:216-566-2902

Emergency Phone Num: (216) 566-2917

CAGE:88573 === Cont

ractor Identification ===

Company Name: THE SHERWIN WILLIAMS CO. DIVERSIFIED BRANDS

Address:101 PROSPECT AVE N.W.

Box:City:CLEVELAND

State:OH ZIP:44115 Country:US

Phone:(800)-832-2541/ EMER: 216-566-2917

CAGE:88573

======= Composition/Information on Ingredients ========

Ingred Name: ETHYLBENZENE

CAS:100-41-4

RTECS #:DA0700000

= Wt:9.

OSHA PEL:435 MG/M3;100 PPM ACGIH TLV:434 MG/M3;100 PPM ACGIH STEL:543 MG/M3;125 PPM

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:XYLENE

CAS:1

330-20-7 RTECS #:ZE2100000 = Wt:51.ACGIH TLV:434 MG/M3;100 PPM ACGIH STEL:651 MG/M3;150 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: TOLUENE 2,4-DIISOCYANATE CAS:584-84-9 RTECS #:CZ6300000 = Wt:.8OSHA PEL:C0.14 MG/M3;C.02 PPM ACGIH TLV:0.036 MG/M3;.005 PPM ACGIH STEL:0.14 MG/M3;0.02 PPM EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS Ingred Name: TOLUENE DIISOCYANATE POLYMER = Wt:40.=========== Hazards Identification ========================== Routes of Entry: Inhalation:YES S kin:YES Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:NO OSHA:NO Health Hazards Acute and Chronic: INHALATION: IRRITATION OF EYES, SKIN & RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. MAY RESULT IN DEATH. Explanation of Carcinogenicity: TOLUENE DIISOCYANATE IS A SUSPECTED HUMAN CARCINOGEN. Effects of Overexposure: IRRITATION, UNCONSCIOUSNESS, HEADACHE, DIZZINESS, NAUSEA, LOSS OF COORDINATION, REDNESS, ITCHING, BURNING SENSATION. Medical Cond Aggravated by Exposure: SENSITIVITY TO ISOCYANATES, LUNG/BREATHING PROBLEMS First Aid:INHALATION: LEAVE THE AREA & GET FRESH AIR. SKIN: WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point:=23.3C, 74.F

Lower Limits:1 Upper Limits:7

Extinguishing Media: CO2, DRY CHEMICAL, FOAM

Fire

Fighting Procedures: USE FULL PROTECTIVE EQUIP/SCBA. WATER SPRAY: INEFFECTIVE. FOG NOZZLES: PREFERABLE. USE WATER TO COOL FIRE EXPOSED CONTAINERS TO PREVENT PRESSURE BUILDUP.

Unusual Fire/Explosion Hazard:KEEP CLOSED CONTAINERS TIGHTLY CLOSED. ISOLATE FROM IGNITION SOURCES. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.

======== Accidental Release Measures ============

Spill Release Pro

cedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE
AREA. ALL PERSONNEL IN THE AREA SHOULD BE PROTECTED. COVER RELEASE
W/ABSORBENT MATERIAL. DEACTIVATE MATERIAL W/A 10% AMMONIUM
HYDROXIDE SOLUTION (HOUSEHOLD AM MONIA) COVER LOOSELY. WASH AREA
W/SOAP & WATER.

Neutralizing Agent: 10% AMMONIUM HYDROXIDE SOLUTION

========== Handling and Storage ==============

Handling and Storage Precautions: KEEP AWAY FROM IGNITION SOURCES.
DURING USE & UNTIL ALL VAPORS ARE GO

NE; KEEP AREA VENTILATED, DON'T

SMOKE. USE APPROVED BONDING & GROUNDING PROCEDURES. KEEP CONTAINERS CLOSED WHEN NOT IN USE. TRANSFE R ONLY TO APPROVED CONTAINERS W/COMPLETE & APPROPRIATE LABELING. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:AVOID CONTACT W/SKIN/EYES/BREATHING VAPOR/SPRAY MIST.
TRANSFER ONLY TO APPROVED CONTAINERS. DON'T TAKE INTERNALLY.
EXTINGUISH FLAMES/PILOT LIGHTS/HEATERS. TURN OFF STOVES/ELEC
TOOLS/APPLIANCES. CONTEN TS ARE FLAMMABLE.

========

=== Exposure Controls/Personal Protection ========

Respiratory Protection:USE NIOSH/MSHA TC19C POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR, WHERE OVERSPRAY IS PRESENT. IF UNAVAILABLE, USE NIOSH/MSHA PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR. USE NIOSH/MSHA RESPIRAT OR, WHEN SANDING/ABRADING THE DRIED FILM.

Ventilation:LOCAL EXHAUST: PREFERABLE. MECHANICAL: ACCEPTABLE IF THE EXPOSURE TO MATERIALS IS MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS.

Protective G

loves:RECOMMENDED Eye Protection:SAFETY GLASSES W/UNPERFORATED SIDESHIELD Other Protective Equipment:BARRIER CREAM Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS AFTER USING. Supplemental Safety and Health BOILING RANGE: 277-292F. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE CONTENTS CAN BE HARMFUL/ FATAL. NO PERSON SHOULD USE THIS PRODUCT/ BE IN THE AREA WHERE IT IS BEING USED, IF TH EY HAVE CHRONIC (LONG TERM) LUNG/ BREA THING PROBLEMS/ IF THEY EVER HAD A REACTION TO ISOCYANATES.
========= Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:277-292F Vapor Density:>1 Spec Gravity:0.96 VOC Grams/Liter:4.8 Evaporation Rate & Defence: SLOWER THAN ETHER Percent Volatiles by Volume:66
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES WATER/ALCOHOLS/AMINES/OTHER COMPOUNDS WHICH REACT W/ISOCYANATES Stability Condition t o Avoid:HEAT, SPARKS, OPEN FLAME, HOT SURFACES/ OTHER SOURCES OF IGNITION Hazardous Decomposition Products:BY FIRE: CO2, CO, OXIDES OF NITROGEN, HYDROGEN CYANIDE
======== Disposal Considerations ===========
Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DON'T INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE W/FED/STATE/LOCAL REGS REGARDING POLLUTION. WASTE MAY BE HAZARDOUS UNDER RCRA & MUST BE TESTED FOR IGNITABI LITY TO DETERMINE EPA
HAZARDOUS WASTE NUMBERS.

============ Other Information ===============

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verif

y and assume responsibility for the suitability of this information to their particular situation.