View NSN Online: https://aerobasegroup.com/nsn/8030-00-900-4412

Product ID:RITE-LOK MILCV-250; MIL-S-22473E GRADE CV (250CC) MSDS Date:11/14/1997 FSC:8030 NIIN:00-900-4412 Status Code:A MSDS Number: CKHKY === Responsible Party === **Company Name: CHEMENCE INC** Address:185 BLUEGRASS VALLEY PKWY City:ALPHARETTA State:GA ZIP:30005 Country:US Emerg ency Phone Num:703-527-3887 Preparer's Name: JAY TATE Chemtrec Ind/Phone:(800)424-9300 CAGE:0ZDS4 === Contractor Identification === **Company Name: CHEMENCE INC** Address:6425 INDUSTRIAL WAY City:ALPHARETTA State:GA ZIP:30201 Country:US Phone:404-664-6624 CAGE:0ZDS4

Ingred Name:POLYGLYCOL DIMETHACRYLATE CAS:25852-47-5 Fraction by Wt: 78%

Ingred Name:BISPHENOL A FUMARATE CAS:39382-25-7 Fraction by Wt: 15%

Ingred Name:CUMENE HYDROP

EROXIDE CAS:80-15-9 RTECS #:MX2450000 Fraction by Wt: 3% EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS
Ingred Name:SACCHARIN CAS:81-07-2 RTECS #:DE4200000 Fraction by Wt: 3% EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS
Ingred Name:N,N-DIALKYLTOLUIDINE CAS:613-48-9 Fraction by Wt: 1%
======================================
Health Hazards Acute and Chronic:THRESHOLD LIMIT VALUE: NO CRITERIA FOR MEASUREMENT. NOT YET ESTABLISHED. EFFECTS OF OVEREXPOSURE: PROLONGED SKIN CO NTACT MAY RESULT IN DERMATITIS IN SENSITIVE PERSONS. MILD SKIN IRRITANT. WILL IRRITAT E EYES ON CONTACT.
======================================
First Aid:WASH WITH SOAP AND WATER FOR SKIN CONTACT. FOR EYE CONTACT, FLUSH WITH PLENTY OF WATER. FOR INGESTION, DO NOT INDUCE VOMITING. CONTACT PHYSICIAN.
======================================
Flash Point Method:TCC Flash Point:>100.C, 212.F Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, WATER Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS Unusual Fire/Explosion Hazard:IRRITATING ORGANIC VAPORS
======================================
Spill Release Procedures:SOAK UP WITH INERT ABSORBENT.
Spill Release Procedures:SOAK UP WITH INERT ABSORBENT.

======= Exposure Controls/P

ersonal Protection ========

Respiratory Protection:NONE NEEDED FOR NORMAL USE.
Ventilation:ENSURE ADEQUATE ROOM VENTILATION FOR COMFORTABLE WORKING CONDITONS.
Protective Gloves:POLYETHYLENE OR RUBBER GLOVES.
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:BARRIER CREAMS RECOMMENDED.
Supplemental Safety and Health

Boiling Pt:>204.4C, 400.F B.P. Text:@ 760 MM Vapor Pres:.01 MM HG Vapor Density:1.01 AIR=1 Sp ec Gravity:1.1 H20=1 VOC Pounds/Gallon:132 Viscosity:100-250 CPS Evaporation Rate & amp; Reference: VERY LOW Solubility in Water: INSOLUBLE Appearance and Odor:BLUE, MILD ORGANIC ODOR Percent Volatiles by Volume:12.0 **Corrosion Rate:NONE** Stability Indicator/Materials to Avoid:YES **AVOID CONTAMINATION** Stability Condition to Avoid: TEMPERATURES IN EXCESS OF 150 DEGREES F. Hazardous Decomposition Products:NONE Conditions to Avoid Polym erization: TEMPERATURES IN EXCESS OF 150 DEGREES F.

Ecological:MARINE POLLUTANT: NONE.

Waste Disposal Methods:LANDFILL OR INCINERATE IN ACCORDANCE WITH EPA AND LOCAL REGULATIONS.

Transport Information:UNRESTRICTED

Disclaimer (provided with this information by the compiling agenc

ies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.