

CONVENTIONAL SEALING MATERIALS, INC -- CONVENTIONAL SCALING MATERIALS --
5330-00-197-8491

=====
Product Identification
=====

Product ID:CONVENTIONAL SCALING MATERIALS

MSDS Date:01/01/1996

FSC:5330

NIIN:00-197-8491

Status Code:A

MSDS Number: CKNSY

=== Responsible Party ===

Company Name:CONVENTIONAL SEALING MATERIALS, INC

Address:558 GARDEN OAK BLVD

City:HOUSTON

Info Phone Num:713-699-0169

Emergency

Phone Num:713-699-0169

CAGE:0R361

=== Contractor Identification ===

Company Name:CONVENTIONAL SEALING MATERIALS, INC

Address:558 GARDEN OAK BLVD

Box:City:HOUSTON

Phone:713-699-0169

CAGE:0R361

=====
Composition/Information on Ingredients
=====

Ingred Name:CHRYBOTILE ASBESTOS

CAS:12001-29-5

RTECS #:CI6478500

= Wt:80.

Ingred Name:VISCOSE RAYON

< Wt:4.5

Ingred Name:STAINLESS STEEL WIRE

< Wt:7.

Ingred Name:GRAPHITE

CAS:7782-42-5

RTECS #:MD9659600

< Wt:4.

OSHA PEL:SEE

TABLE Z-3
ACGIH TLV:2 MG/M3

Ingred Name:NATURAL RUBBER
CAS:9006-04-6
< Wt:3.

Ingred Name:POLIVINYL ACETATE
< Wt:3.

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:A CONCEIVABLE HEALTH HAZARD WOULD BE
FROM THE RELEASE OF ASBESTOS FIBERS INTO THE AIR BY DELIBERATELY
MIS-HANDLING SUCH AS, SAWING, SANDING, DRILLING, O
R GRINDING. DO
NOT PERFORM THESE OPERATIONS ON T HIS MATERIAL. IF ANY OF THESE
OPERATIONS ARE PERFORMED, USE ADEQUATE DUST EXTRACTION/SUPPRESSION
PROCEDURES. IGNITION OF THIS MATERIAL MAY RESULT IN POLYMER FUME
FEVER.
Explanation of Carcinogenicity:CONTAINS ASBESTOS.
Effects of Overexposure:POLYMER FUME FEVER.

=====
===== First Aid Measures =====

First Aid:MOVE AFFECTED PERSON TO FRESH AIR AND SEEK IMMEDIATE MEDICAL
TREATMENT.

=====
===== Fire Fighting Measures =====

Extinguishing Media:MAY BE WATER OR FOAM.
Fire Fighting Procedures:THIS MATERIAL HAS LITTLE OR NO COMBUSTIBILITY.
ASBESOS PARTICULATE MAY BE RELEASED IN A FIRE. FIREFIGHTERS SHOULD
USE A SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES
INVOLVING THIS MATERIAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID DUST.

=====
===== Exposure Controls/Personal Protec

tion =====

Respiratory Protection:WHEN CHANGING DETERIORATED PACKING, WE SUGGEST WETTING MATERIAL TO PREVENT AIRBORNE FIBER DISPERSAL. OR WEAR MASK TO PREVENT INHALING ANY DUST MATERIAL.

Ventilation:USE LOCAL EXHAUST.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:T6

Spec Gravity:2.2 - 2.4

Solubility in Water:INSOLUBLE

Appearance and Odor:BLACK COLOR, SLIPPERY SQUARE ROPE-LIKE MATERIAL.

===== Stability and
Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:THIS IS A STABLE MATERIAL UNDER NORMAL USE, HANDLING, AND STORAGE. SHELF LIFE IS MEASURED IN YEARS.

===== Disposal Considerations =====

Waste Disposal Methods:BURY WASTES IN SOLID LANDFILL AS REQUIRED IN 29 CFR 1910-1001. ALSO COMPLY WITH APPLICABLE STATE AND LOCAL REGULATIONS. WASTES SHOULD BE IN A SCALED CONTAINER MARKED WITH APPROPRIATE

WARNING LABEL. HIGH TEMPERATURE INCINERATION MAY BE AN OPTION. CHECK STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.