

VALVOLINE OIL -- TECTYL 846, CLASS I -- 8030-01-340-4866

===== Product Identification =====

Product ID:TECTYL 846, CLASS I

MSDS Date:02/10/1995

FSC:8030

NIIN:01-340-4866

Status Code:A

MSDS Number: CKSGH

=== Responsible Party ===

Company Name:VALVOLINE OIL

Address:3499 DABNEY DRIVE

Box:14000

City:LEXINGTON

State:KY

ZIP:40512

Country:US

Info Phone Num:606-357-7847/606-264-7000

Emergency Phone Num:80

0-ASHLAND/800-274-5263

CAGE:72527

=== Contractor Identification ===

Company Name:ADIRONDACK ELECTRONICS INC

Address:1991 CENTRAL AVENUE

Box:City:ALBANY

State:NY

ZIP:12205

Country:US

Phone:518-456-0203

Contract Num:N00104-97-G-7002-6481

CAGE:1A737

Company Name:VALVOLINE OIL CO

Address:3499 BLAZER PKY

Box:14000

City:LEXINGTON

State:KY

ZIP:40512

Country:US

Phone:606-357-7206 / 800-274-5263

CAGE:72527

===== Composition/Information on Ingredients =====

Ingred Name:RUSTPROOFING COM

POUND

Minumum % Wt:55.

Maxumum % Wt:60.

Other REC Limits:NONE RECOMMENDED

Ingred Name:ALIPHATIC HYDROCARBON, (STODDARD TYPE)

CAS:8052-41-3

RTECS #:WJ8925000

Minumum % Wt:40.

Maxumum % Wt:45.

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM; 9596

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

He

alth Hazards Acute and Chronic:EYES: IRRITATION. SKIN: IRRITATION,

REPEATED CONTACT MAY DRY SKIN AND CAUSE ALLERGIC SKIN REACTION.

INHALATION: SMALL AMOUNTS NOT LIKELY TO CAUSE HARMFUL EFFECTS.

LARGE AMOUNTS MAY BE HARMFUL. INGESTI ON: SMALL AMOUNTS NOT LIKELY TO CAUSE HARMFUL EFFECTS. LARGE AMOUNTS MAY BE HARMFUL. ASPIRATION HAZARD.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES: IRRITATION, STINGING, SWELLING. SKIN:

IRRITATION, REDNESS, DRYING, BURNS,

SKIN DAMAGE, ALLERGIC SKIN

REACTION, RASH, BLISTERING, SCALING. INHALATION: IRRITATION OF

NOSE, THROAT, AIRWAYS, CNS DE PRESSION, DIZZINESS, DROWSINESS,

NAUSEA, UNCONSCIOUSNESS, DEATH. INGESTION: STOMACH/INTESTINAL

UPSET, NAUSEA, DIARRHEA.

Medical Cond Aggravated by Exposure:CNS EFFECTS.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF SYMPTOMS DEVELOP, GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATE

D CLOTHING. WASH

SKIN WITH SOAP AND WATER. IF SYMPTOMS PERSIST, GET MEDICAL ATTENTION. INHALATION: MOVE TO FRESH AIR. IF NOT BREATHING, GIVE CPR. IF BREATHING DIFFICULT GIVE OXYGEN. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING, LAY PATIENT ON LEFT SIDE. GET MEDICAL HELP.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:=-41.1C, 106.F

Lower Limits:1.0

Extinguishing Media:REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:WATER OR FOAM MAY CAUSE FROTHING AND ENDANGER THE LIFE OF FIREFIGHTER. USE SCBA WITH FULLFACE PIECE OPERATED IN POSITIVE PRESSURE DEMAND MODE AND TURN-OUT GEAR & CHEMICAL RESISTANT PERSONAL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:VAPORS, HEAVIER THAN AIR, MAY TRAVEL TO DISTANT IGNITION SOURCE AND FLASH BACK. NEVER USE WELDING/CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY), WHICH MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB SMALL SPILLS ON ABSORBENTS. LARGE SPILLS: ELIMINATE IGNITION SOURCES. STOP SPILL, DIKE AREA. PREVENT FROM ENTERING DRAINS, SEWERS, STREAMS, OR OTHER BODIES OF WATER. RECOVER LIQUID TO SALVAGE. IF RUN-OFF OCCURS, NOTIFY AUTHORITIES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM SOURCES OF IGNITION. USE

AND STORE IN AREAS WITH ADEQUATE VENTILATION. GROUND/BOND ALL 5-GAL AND LARGER CONTAINERS WHEN TRANSFERRING.

Other Precautions:EMPTY CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS DUE TO RETAINED RESIDUES (VAPOR, LIQUID, SOLID). DO NOT USE CUT/WELD TORCH ON CONTAINERS (EVEN EMPTY).

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RECOMMEND USING NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IF WORKPLACE EXPOSURE LIMITS ARE EXCEEDED. ENGINEER

RING
OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:WEAR IMPERVIOUS GLOVES.

Eye Protection:CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:WEAR NORMAL WORK CLOTHING COVERING ARMS AND LEGS.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

APPLICABLE SPECS: MIL-C-16173E, CLASS 1, GRADE 4.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:=157.2C, 315.F

Vapor Pres:2.0 MM HG

Vapor Density:1 (AIR=1)

Spec Gravity:0.870

Evaporation Rate & Reference:SLOWER THAN ETHYL ETHER

Appearance and Odor:LIQUID. AMBER COLOR.

Percent Volatiles by Volume:40-46

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YE

S

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:MAY FORM: CARBON DIOXIDE, CARBON MONOXIDE, SULFUR COMPOUNDS, VARIOUS HYDROCARBONS.

Conditions to Avoid Polymerization:WILL NOT UNDERGO HAZARDOUS POLYMERIZATION.

===== Disposal Considerations =====

Waste Disposal Methods:TRANSFER CONTAMINATED PRODUCT/ABSORBENT TO CONTAINERS FOR DISPOSAL. DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL, STATE

AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.