

UNIMARK OIL COMPANY (FORMERLY -- GARD HIGH PERFORMANCE SAE 10W-30 (QUART))

=====
MSDS Safety Information
=====

FSC: 9150
NIIN: 01-413-6897
MSDS Date: 03/24/1998
MSDS Num: CKZGG
Product ID: GARD HIGH PERFORMANCE SAE 10W-30 (QUART)
MFN: 03
Responsible Party
Cage: 3K676
Name: UNIMARK OIL COMPANY (FORMERLY GARD OIL)
Address: 2727 R
OE LANE
City: KANSAS CITY KS 66103-1543
Info Phone Number: 913-236-5000; FX 913-236-4419
Emergency Phone Number: 913-236-5000
Preparer's Name: MICHAEL S. MCLEMORE
Chemtrec IND/Phone: (800)424-9300
Proprietary Ind: Y
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 3K676
Name: UNIMARK OIL COMPANY (FORMERLY GARD OIL)
Address: 2727 ROE LANE
City: KANSAS CITY KS 66103-1543
Phone: 913-2
36-5000; FX 913-236-4419

=====
Item Description Information
=====

Item Manager: S9G
Item Name: LUBRICATING OIL,ENGINE
Unit of Issue: BX
Quantitative Expression: 00000000012QT
UI Container Qty: 1
Type of Container: BOX OF 12

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====

Health Hazards Data

=====

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: EYE CONTACT: NOT NORMALLY EXPECTED TO CAUSE IRRITATION. PROLONGED CONTACT MAY CAUSE MILD EYE DISCOMFORT, TEARING, OR BLURRING OF VISION. SKIN CONTACT: NOT EXPECTED TO CAUSE IRRITATION. PROLONGED OR REPEATED CONTACT MAY LEAD TO ALLERGIC SKIN SENSITIZATION AND DERMATITIS (DRYNESS, CH

APPING AND REDDENING OF SKIN). INHALATION: OVEREXPOSURE OF HOT MATERIAL MAY CAUSE NONSPECIFIC DISCOMFORT, NAUSEA, HEADACHE, OR WEAKNESS. INGESTION: NON-TOXIC UNLESS LUNG ASPIRATION OCCURS. ASPIRATION LEADS TO CHEMICAL PNEUMONITIS, PULMONARY EDEMA AND HEMMORRHAGE. MAY BE FATAL. PRODUCT HAS LAXATIVE PROPERTIES AND MAY RESULT IN ABDOMINAL CRAMPS AND DIARRHEA.

Explanation Of Carcinogenicity: NONE OF THE OILS IN THIS PRODUCT REQUIRE A CANCER WARNING UNDER OSHA (29 CFR 1910.1200). THESE OILS HAVE NOT BEEN LISTED

IN THE NTP ANNUAL REPORT NOR HAVE THEY BEEN CLASSIFIED BY IARC AS CARCINOGENIC TO HUMANS (GROUP 1), PROBABLY CARCINOGENIC TO HUMANS (GROUP 2A), OR POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B).

Signs And Symptoms Of Overexposure: EYES: MILD EYE DISCOMFORT, TEARING, BLURRING OF VISION. SKIN: ALLERGIC SKIN SENSITIZATION, DERMATITIS, DRYNESS, CHAPPING, REDDENING. INHALATION: DISCOMFORT, NAUSEA, HEADACHE, WEAKNESS. INGESTION: NON-TOXIC UNLESS LUNG ASPIRATION OCCURS

. ASPIRATION LEAD TO CHEMICAL PNEUMONITIS, PULMONARY EDEMA, HEMMORRHAGE, AND MAY BE FATAL. SIGNS OF LUNG INVOLVEMENT: INCREASED RESPIRATORY RATE, INCREASED HEART RATE, BLUISH DISCOLORATION OF SKIN, COUGHING, CHOKING, GAGGING, GASTROINTESTINAL DISCOMFORT, VOMITING. PRODUCT HAS LAXATIVE PROPERTIES RESULTING IN ABDOMINAL CRAMPS AND DIARRHEA.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER, CONTINUE UNTIL

IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CALL A PHYSICIAN. IF MATERIAL IS HOT, TREAT FOR THERMAL BURNS AND TAKE VICTIM TO HOSPITAL. SKIN CONTACT:

REMOVE CONTAMINATED CLOTHING AND LAUNDRY BEFORE REUSE. WASH EXPOSED SKIN AREA

WITH SOAP AND WATER. IF REDNESS OR IRRITATION OCCURS, SEEK MEDICAL ATTENTION. IF MATERIAL IS HOT, SUBMERGE INJURED AREA IN COLD WATER. IF VICTIM IS SEVERELY BURNED, REMOVE TO HOSPITAL. INHALATION: MOVE TO FRESH AIR. USE OXYGEN IF BREATHING IS DIFFICULT OR AIR

TIFICAL RESPIRATION IF NOT
BREATHING. SEEK MEDICAL (CONTD. SEE "ECOLOGICAL")

=====
Handling and Disposal
=====

Spill Release Procedures: TURN OFF SOURCES OF IGNITION. EVACUATE AND VENTILATE
AREA. PERSONNEL WEARING PROTECTIVE EQUIPMENT SHOULD CONTAIN SPILL WITH INERT
MATERIALS. PREVENT MATERIAL FROM ENTERING SEWERS OR WATERWAYS. IF A LARGE
SPILL OCCURS NOTIFY APPROPRIATE AUTHORITIES. PICK UP DIKED SPILL USING
EXPLOSION PROOF, NON-SPARKING VACUUM PUMPS, SHOVELS, OR BUCKETS, AND DISPOSE
OF IN SUITABLE CONTAINERS.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: UNDER RCRA IT IS RESPONSIBILITY OF USER TO DETERMINE AT
TIME OF DISPOSAL WHETHER PRODUCT MEETS RCRA CRITERIA FOR HAZARDOUS WASTE.
WASTE MANAGEMENT SHOULD BE IN FULL COMPLIANCE WITH FEDERAL, STATE, AND LOCAL
LAWS. CONTACT LOCAL ENVIRONMENTAL OR HEALTH AUTHORITIES FOR APPROVED DISPOSAL

OF THIS MATERIAL. MOST USED OIL IS RECLAIMED OR INCINERATED.

Handling And Storage Precautions: KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO
NOT TRANSFER TO UNMARKED CONTAINERS. FIRE EXTINGUISHERS SHOULD BE KEPT
READILY AVAILABLE. STORE CONTAINERS AWAY FROM HEAT, SPARKS, OPEN FLAME, OR
OXIDIZING MATERIALS.

Other Precautions: SEE NFPA 30 AND OSHA 1910.106--FLAMMABLE AND COMBUSTIBLE
LIQUIDS. EMPTY CONTAINERS RETAIN PRODUCT RESIDUE WHICH MAY EXHIBIT HAZARDS OF
MATERIAL, THEREFORE DO NOT
RESSURIZE, CUT, GLAZE, WELD OR USE FOR ANY OTHER
PURPOSES. RETURN DRUMS TO RECLAMATION CENTERS FOR PROPER CLEANING AND REUSE.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: COC

Flash Point: =210.C, 410.F

Autoignition Temp Text: N/D

Lower Limits: N/D

Upper Limits: N/D

Extinguishing Media: USE DRY CHEMICAL, FOAM, WATER FOG, CARBON DIOXIDE.

Fire Fighting Procedures: WATER MAY

BE INEFFECTIVE BUT MAY BE USED TO COOL

CONTAINERS EXPOSED TO HEAT OR FLAME. CAUTION SHOULD BE EXERCISED WHEN USING
WATER OR FOAM; FROTHING MAY OCCUR, ESPECIALLY IF SPRAYED INTO CONTAINERS OF
HOT, BURNING LIQUID.

Unusual Fire/Explosion Hazard: DENSE SMOKE MAY BE GENERATED WHILE BURNING.

TOXIC FUMES, GASES OR VAPORS MAY EVOLVE ON BURNING. HEAVY FLAMMABLE VAPORS
MAY SETTLE ALONG GROUND LEVEL AND LOW SPOTS TO CREATE AN INVISIBLE FIRE
HAZARD. THE VAPORS MAY EXTEND TO SOURCES OF IGNITION

TION AND FLASH BACK. CARE
SHOULD ALWAYS BE EXERCISED IN DUST/ MIST AREAS.

=====
Control Measures
=====

Respiratory Protection: NONE REQUIRED IF AIRBORNE CONCENTRATIONS ARE MAINTAINED BELOW THRESHOLD LIMITS. OTHERWISE A RESPIRATORY PROTECTION PROGRAM MEETING OSHA 1910.134 AND ANZI ZB8.2 REQUIREMENTS MUST BE FOLLOWED. WHERE MISTING MAY OCCUR, WEAR AN MSHA/NIOSH APPROVED (OR EQUIVALENT) HALF-MASK FORM

DUST/MIST AIR PURIFYING RESPIRATOR.

Ventilation: MECHANICAL METHODS SUCH AS FUME HOODS OR AREA FANS MAY BE USED TO REDUCE LOCALIZED VAPOR/MIST AREAS.

Protective Gloves: NEOPRENE OR NITRILE RUBBER, TO AVOID SKIN SENSITIZATION AND ABSORPTION.

Eye Protection: SAFETY GLASSES WITH SIDE SHIELDS OR VENTED/SPLASH PROOF GOGGLES.

Other Protective Equipment: USE OF AN APRON AND OVER-BOOTS OF CHEMICALLY IMPERVIOUS MATERIALS, NEOPRENE OR NITRILE RUBBER RECOMMENDED TO AVOID SKIN SENSIT

IZATION. IF HANDLING HOT MATERIAL USE INSULATED PROTECTIVE EQUIPMENT.

Work Hygienic Practices: CONSUMPTION OF FOOD AND DRINK SHOULD BE AVOIDED IN WORK AREAS WHERE PRODUCT IS PRESENT. ALWAYS WASH HANDS AND FACE WITH SOAP AND

WATER BEFORE EATING, DRINKING, OR SMOKING.

Supplemental Safety and Health: IF VAPOR OR MIST IS GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, ADEQUATE VENTILATION IN ACCORDANCE WITH GOOD ENGINEERING PRACTICE MUST BE PROVIDED TO MAINTAIN CONCENTRATIONS BELOW THE

SPECIFIED EXPOSURE. EYEWASH STATIONS AND SHOWERS SHOULD BE AVAILABLE IN AREAS WHERE THIS MATERIAL IS USED AND STORED.

=====
Physical/Chemical Properties
=====

HCC: V6

Boiling Point: >260.C, 500.F

B.P. Text: EXPECTED TO BE

Vapor Pres: NEGLIGIBLE 25C AT 1 ATM.

Vapor Density: > 1 AT STP

Spec Gravity: 0.877 AT 15.6C(60F)

Viscosity: 10.9 CST AT 100C(212F)

Evaporation Rate & Reference: NEGL

IGIBLE AT STP

Solubility in Water: NEGLIGIBLE.

Appearance and Odor: AMBER, CLEAR FLUID, MILD PETROLEUM HYDROCARBON ODOR.

Percent Volatiles by Volume: NEGLI AT STP

Corrosion Rate: UNKNOWN

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: MATERIAL STABLE AT ROOM TEMPERATURE AND PRESSURE.
AVOID HIGH TEMPERATURES AND PRODUCT CONTAMINATION.

Materials To Avoid: AVOID

CONTACT WITH ACIDS AND OXIDIZING MATERIALS.

Hazardous Decomposition Products: SMOKE, CARBON MONOXIDE AND DIOXIDE, AND OTHER ALDEHYDES OF INCOMPLETE COMBUSTION.OXIDES OF CARBON, ZINC, CALCIUM, MAGNESIUM, PHOSPHORUS AND SULFUR, HYDROGEN SULFIDE, ALKYL MERCAPTANS, OTHER SULFIDES.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NONE. WILL NOT OCCUR.

=====
Toxicological Information
=====

Toxicological Information: PRODUCT CONTAINS ZINC ALKYL DITHIOPHOSPHATES (ZDP). SEVERAL ZDPS HAVE BEEN REPORTED TO HAVE WEAK MUTAGENIC ACTIVITY IN CULTURED MAMMALIAN CELLS BUT ONLY AT CONCENTRATIONS THAT WERE TOXIC TO THE TEST CELLS. WE DO NOT BELIEVE THAT THERE IS ANY MUTAGENIC RISK TO WORKERS EXPOSED TO THIS PRODUCT'S CONCENTRATION LEVEL OF ZDP. NONE OF THE OILS REQUIRE A CANCER WARNING UNDER OSHA, 29 CFR 1910.1200. NOT LI STED IN NTP ANNUAL REPORT, NOR CLASSIFI ED BY IARC AS CARCINOGENIC TO HUMANS (GROUP 1), NOR PROBABLY CARCINOGENIC TO HUMANS (GROUP 2A) NOR POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B).

=====
Ecological Information
=====

Ecological: ENVIRONMENTAL TOXICITY:THIS MATERIAL MAY BE TOXIC TO AQUATIC ORGANISMS AND SHOULD BE KEPT OUT OF SEWAGE AND DRAINAGE SYSTEMS AND ALL BODIES OF WATER. ENVIRONMENTAL FATE: NO DATA AVAILABLE. (CONTD. FRO M "FIRST AID") ATTENTION IF NECESSARY. INGESTION: DO NOT INDUCE VOMITING DUE TO ASPIRATION HAZARD. IMMEDIATELY GIVE 2 GLASSES OF WATER. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IF VOMITI NG OCCURS LOWER HEAD BETWEEN KNEES TO AVOID ASPIRATION. SEEK IMMEDIATE MEDICAL ATTENTION.

=====
MSDS Transport Information
=====

Regul

atory Information

Sara Title III Information: SARA TITLE III: SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCES: NONE. SECTION 311, 312 HAZARD CATEGORIZATION: ACUTE (IMMEDIATE HEALTH EFFECTS): YES; CHRONIC (DELAYED HEALTH EFFECTS): NO; FIRE (HAZARD): NO; REACTIVITY (HAZARD): NO; PRESSURE (SUDDEN RELEASE HAZARD): NO. SECTION 313 TOXIC CHEMICALS: ZINC <0.10%.

Other Information

Other Information: NFPA 704 RATING: HEALTH: 1 (SLIGHT); FIRE: 1 (SLIGHT); REACTIVITY: 0 (MINIMAL); SPECIFIC HAZARD: NONE; PROTECTIVE INDEX: N/A. NPCA-RATING: HEALTH: 1 (SLIGHT); FIRE: 1 (SLIGHT); REACTIVITY:0 (MINI MAL); SPECIFIC HAZARD: N/A; PROTECTION INDEX: B. PRECAUTIONARY LABELS: WARNING: NONE REQUIRED. CLEAN WATER ACT/OIL POLLUTION ACT: SECTION 311 OF CLEAN WATER ACT (40 CFR 110) AND OIL POLLUTION CONTROL A CT OF 1990, TH IS MATERIAL IS CONSIDERED AN OIL. SPILLS OR DISCHARGES THAT PRODUCE A SHEEN OR FILM ON WATER SURFACE, WATERWAYS, DITCHES, SEWERS LEADING TO SURFACE WATER MUST BE REPORTED. CONTACT NATION AL RESPONSE CENTER AT 800-424-8802.

Transportation Information

Responsible Party Cage: 3K676
Trans ID NO: 156121
Product ID: GARD HIGH PERFORMANCE SAE 10W-30 (QUART)
MSDS Prepared Date: 03/24/19
98
Review Date: 03/01/2001
MFN: 3
Net Unit Weight: 22 LBS
Multiple KIT Number: 0
Unit Of Issue: BX
Container QTY: 1
Type Of Container: BOX OF 12
Additional Data: TRANSPORTATION DATA PER MANUFACTURER'S MSDS.

Detail DOT Information

DOT PSN Code: ZZZ
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail IMO I

nformation

=====

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

=====

Detail IATA Information

=====

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====

Detail AFI Information

=====

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====

HAZCOM Label

=====

Product ID: GARD HIGH PERFORMANCE SAE 10W-30 (QUART)

Cage: 3K676

Company Name: UNIMARK OIL COMPANY (FORMERLY GARD OIL)

Street: 2727 ROE LANE

City: KANSAS CITY KS

Zipcode: 66103-1543

Health Emergency Phone: 913-236-5000

Label Required IND: Y

Date Of Label Review:

03/01/2001

Status Code: A

Label Date: 03/01/2001

Origination Code: F

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: CAUTION

Respiratory Protection IND: YES

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: Slight

Reactivity Hazard: None

Hazard And Precautions: EYE CONTACT: NOT EXPECTED TO CAUSE IRRITATION.

PROLONGED CONTACT MAY CAUSE MILD DISCOMFORT, TEARING, BLURRING OF VISION.

SKIN CONTACT: NOT EXPECTED TO CAUSE IRRITATION. PROLONGED OR REPEATED CONTACT

MAY LEAD TO

O ALLERGIC SENSITIZATION, DERMATITIS (DRYNESS, CHAPPING AND REDDENING OF SKIN). INHALATION: HOT VAPORS MAY CAUSE NONSPECIFIC DISCOMFORT, NAUSEA, HEADACHE, WEAKNESS. INGESTION: NON-TOXIC UNLES S LUNG ASPIRATION OCCURS. ASPIRATION LEADS TO CHEMICAL PNEUMONITIS, PULMONARY EDEMA AND HEMMORRHAGE. MAY BE FATAL. PRODUCT HAS LAXITIVE PROPERTIES AND MAY RESULT IN ABDOMINAL CRAMPS AND DIARRHEA.

=====

Disclaimer (provided with this information by the compiling agencies): This

information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utili

zing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.