

BEACON CHEMICAL COMPANY, INC. -- MAGNATAC M611 -- 8040-00-200-4390

===== Product Identification =====

Product ID:MAGNATAC M611
MSDS Date:06/01/1995
FSC:8040
NIIN:00-200-4390
Status Code:A
Kit Part:Y
MSDS Number: CLBMB
=== Responsible Party ===
Company Name:BEACON CHEMICAL COMPANY, INC.
Address:125 MACQUESTEN PARKWAY
City:MOUNT VERNON
State:NY
ZIP:10550
Country:US
Info Phone Num:914-699-3400
Emergency Phone Num:(800)424-9300
Chemtrec Ind/Phone:(800)424-9300
C
AGE:5B981
=== Contractor Identification ===
Company Name:BEACON CHEMICAL COMPANY, INC.
Address:125 MACQUESTEN PARKWAY
Box:City:MOUNT VERNON
State:NY
ZIP:10550
Country:US
Phone:914-699-3400
CAGE:5B981

===== Composition/Information on Ingredients =====

Ingred Name:ALLYL GLYCIDYL ETHER
CAS:106-92-3
RTECS #:RR0875000
< Wt:5.

===== Hazards Identification =====

Health Hazards Acute and Chronic:EYES: CAN CAUSE IRRITATION, REDNESS,
TEARING,

BLURRED VISION. SKIN: CONTACT CAN CAUSE MODERATE IRRITATION. PROLONGED OR REPEATED CONTACT CAN CAUSE SENSITIZATION. INHALATION: NOT LIKELY DUE TO LOW VOLATILITY OF THE MATERIAL.

Medical Condition Aggravated by Exposure:

===== First Aid Measures =====

First Aid: IF ON SKIN: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. IF POLYMER PERSISTS ON SKIN, WASH WITH ISOPROPYL ALCOHOL. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. IF IN EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY GET MEDICAL ATTENTION. IF SWALLOWED: DO NOT INDUCE VOMITING, KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point: >148.9C, 300.F
300F

Extinguishing Media: FOAM, CARBON DIOXIDE OR DRY CHEMICAL

Fire Fighting Procedures: THE USE OF SCBA IS RECOMMENDED FOR FIRE FIGHTERS. WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIA, BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL.

===== Accidental Release Measures =====

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN COMPLETED. STOP SPILL AT SOURCE AND DIKE AREA, SHOVEL INTO SALVAGE OR WASTE CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NOT ORDINARILY REQUIRED.

Ventilation:

PROVIDE SUFFICIENT MECHANICAL (GENERAL/LOCAL EXHAUST) VENTILATION.

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: WEAR IMPERVIOUS CLOTHING AND BOOTS.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Spec Gravity: 1.020

VOC Grams/Liter: 8.5

Appearance and Odor: HEAVY GRAY PASTE

Percent Volatiles by Volume: 0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AMINES

,ANHYDRIDES, EPOXY CURRING AGENTS.

Stability Condition to Avoid:PREMATURE MIXING EITH ECURING AGENTS.

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE AND
VARIOUS HYDROCARBONS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN A LANDFILL IN ACCORDANCE WITH
LOCAL, STATE AND FEDERAL REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the com
piling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.