

CENTURY LUBRICANTS CO, NFO TECHNOLOGIES DIV -- CHEMPLEX 1381 -- 6850-00-281-4033
===== Product Identification =====

Product ID:CHEMPLEX 1381
MSDS Date:07/18/1997
FSC:6850
NIIN:00-281-4033
Status Code:A
MSDS Number: CLDFX
=== Responsible Party ===
Company Name:CENTURY LUBRICANTS CO, NFO TECHNOLOGIES DIV
Address:2140 S. 88TH STREET
City:KANSAS CITY
State:KS
ZIP:66111-8701
Country:US
Info Phone Num:9
13-422-4022/ 800-800-6457
Emergency Phone Num:913-791-3645
Resp. Party Other MSDS Num.:DOC 498 188002-AA
Preparer's Name:M.D. HART
CAGE:0BF03
=== Contractor Identification ===
Company Name:CENTURY LUBRICANTS CO, NFO TECHNOLOGIES DIV
Address:2140 S. 88TH STREET
Box:City:KANSAS CITY
State:KS
ZIP:66111-8701
Country:US
Phone:913-422-4022/ 800-800-6457
CAGE:0BF03
Company Name:INLAND PACKAGING INC
Address:209 PETERSON DR
Box:644
City:ELIZABETHTOWN
State:KY
ZIP:42701-9804
Country:US
Phone:502-737-6757

Contract Num:SP0450-01-M-ZC30
CAGE:66172

===== Composition/Information on Ingredients =====

Ingred Name:SILICA THICKNER
OSHA PEL:20 MPPCF (DUST)

Ingred Name:ZINC COMPOUND
CAS:7440-66-6
RTECS #:ZG8600000
< Wt:80.
ACGIH TLV:5 MG/M3
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CHRONIC: NONE EXPECTED.
Explanation of Carcinog
enicity:NOT LISTED.
Effects of Overexposure:EYES: NONE EXPECTED. SKIN: PROLONGED OR
REPEATED CONTCAT MAY CAUSE MILD IRRITATION. INHALATION: NONE
EXPECTED. INGESTION: NONE EXPECTED.

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER. SEE PHYSICIAN. SKIN: WASH WITH SOAP
AND WATER. IF HIGH PRESSURE, GET IMMEDIATE MEDICAL ATTENTION.
INHALTION: REMOVE FROM CONTAMINATED AREA. COMMENTS: TREAT ACCORDING
TO PERSON'S CONDITION AND S
PECIFICS OF EXPOSURE. DO NOT HANDLE
NEAR HEAT, FLAMES OR SPARKS.

===== Fire Fighting Measures =====

Flash Point:=101.7C, 215.F
Autoignition Temp:Autoignition Temp Text:UNK
Lower Limits:UNK
Upper Limits:UNK
Extinguishing Media:DRY CHEMICAL, COA2, WATER SPRAY, FOAM.
Fire Fighting Procedures:AVOID BREATHING VAPORS. USE BREATHING
APPARATUS IN CONFINED AREAS. COOL EXPOSED CONTAINERS WITH
WATERSPRAY.
Unusual Fire/Explosion Hazard:SILICON DIOXIDE, CARBON

OXIDES,
FORMALDEHYDE, UNVENTED ORGANIC COMPOUNDS.

===== Accidental Release Measures =====

Spill Release Procedures:ADD ABSORBENT TO SPILL AREA. KEEP SILICONE PRODUCTS OUT OF SEWERS AND WATERWAYS. ADVISE AUTHORITIES IF THEY DO NOT ENTER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE NEAR HEAT, FLAMES, SPARKS. DO NOT WELD OR HEAT EMPTY CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED.
Ventilation:GEREAL ADEQUATE. USE LOCAL MECHANICAL TO INSURE TLV'S NOT SURPASSED WHERE APPLICABLE.
Protective Gloves:CHEMICAL RESISTANT DESIRABLE.
Eye Protection:GOGGLES OR FACESHIELD DESIRABLE.
Other Protective Equipment:NONE NORMALLY NEEDED.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V5
Boiling Pt:=315.6C,
600.F
Vapor Pres:NIL
Vapor Density:>1
Spec Gravity:>1.0
Evaporation Rate & Reference: