View NSN Online: https://aerobasegroup.jp/nsn/6140-01-440-4837

OPTIMA BATTERIES INC -- SEALED LEAD ACID BATTERY

MSDS Safety Information

FSC: 6140

NIIN: 01-440-4837 MSDS Date: 12/15/2000 MSDS Num: CLHCC

Product ID: SEALED LEAD ACID BATTERY

MFN: 01 Article: Y

Responsible Party Cage: 0UJ55

Name: OPTIMA BATTERIES INC Address: 17500 E 22ND AVENUE

City: AUROR A CO 80011

Info Phone Number: 303-340-7400

Emergency Phone Number: 800-434-9300 Resp. Party Other MSDS No.: OBI-0001G Chemtrec IND/Phone: (800)424-9300

Published: Y

Contractor Summary

Cage: 0UJ55

Name: OPTIMA BATTERIES INC Address: 17500 E 22ND AVENUE

City: AURORA CO 80011

Phone: 303-448-8899 OR 800-292-4359

Item Description Info

rmation

Item Manager: S9G

Item Name: BATTERY, STORAGE

Unit of Issue: EA

Regulated Components

Regulated Component Name: SULFURIC ACID ELECTROLYTE

CAS: 7664-93-9 Percent Text: 17-25%

Regulated Component Name: CASE MATERIAL POLYPROPYLENE

CAS: 9003-07-0 Percent Text: 2-6%

Regulated Component Name: SEPERATOR/PASTER PAPER FIBROUS GLASS

CAS: 65997-17-3 Percent Text: 1-4%

Regulated Component Name: LEAD COMPOUNDS

CAS: 7439-92-1 Percent Text: 63-81%

Health Hazards Data

Carcinogenicity Inds - NTP: NO

IARC: NO

Effects of Exposure: POTENTIAL HEALTH EFFECTS: NONE EXPECTED FOR FINISHED PRODUCT UNDER NORMAL CONDITIONS OF USE. CHRONIC EXPOSURE: NONE EXPECTED FOR FINISHED PRODUCT UNDER NORMAL CONDITIONS OF USE.

Explanation

Of Carcinogenicity: FOR FINISHED PRODUCT UNDER NORMAL CONDITIONS OF USF.

Signs And Symptions Of Overexposure: SIGNS AND SYMPTOMS OF ACUTE EXPOSURE: NONE EXPECTED FOR FINISHED PRODUCT UNDER NORMAL CONDITIONS OF USE. EFFECTS OF OVEREXPOSURE: NO EXPOSURE EXPECTED FOR FINISHED PRODUCT. HOWEVER, DO NOT PUNCTURE O R OPEN BATTERY CASE. ACID ELECTROLYTE MAY BE RELEASED. USE ONLY STANDARD CHARGING METHODS. IF OVERCHARGED, BATTERY MAY RELEASE GASES HYDOGEN

AND OXYGEN).

Medical Cond Aggravate

d By Exposure: NONE EXPECTED FOR FINISHED PRODUCT UNDER NORMAL CONDITIONS OF USE.

First Aid: INHALATION-NOT EXPECTED FOR PRODUCT UNDER NORMAL CONDITIONS OF USE. HOWEVER, IF ACID VAPOR IS RELEASED DUE TO OVERCHARGING/ABUSE OF THE BATTERY, REMOVE EXPOSED PERSON TO FRESH AIR. IF BREATHING IS DIF FICULT, OXYGEN MAY BE GIVEN. IF BREATHING HAS STOPPED, ARTIFICIAL RESPIRATION SHOULD BE STARTED IMMEDIATELY. SEEK MEDICAL AID. EYES-EXPOSURE NOT EXPECTED FOR PRODUCT UNDER NORMAL CONDITIONS OF U

SE. HO WEVER, IF ACID FROM BROKEN BATTERY CASE ENTERS
EYES, FLUSH WITH WATER FOR 15 MINS. IF IRRITATION DEVELOPS, SEEK PROMPT
MEDICAL AID. SKIN-EXPOSURE NOT EXPECTED FOR PRODUCT UNDER NORMAL CONDITIONS
OF US E. INGESTION-SEEK PROMPT MEDICAL AID.

Handling and Disposal

Spill Release Procedures: AVOID CONTACT WITH ACID MATERIALS. USE SODA ASH, BAKING SODA OR LIME TO NEUTRALIZE ACI

D IF RELEASED.

Neutralizing Agent: USE SODA ASH, BAKING SODA OR LIME.

Waste Disposal Methods: SEND TO A LEAD RECYCLING FACILITY THAT FOLLOWS

APPLICABLE FEDERAL, STATE & DISTRIBUTOR FOR ROUTINE DISPOSITION OF SPENT OR DAMAGED BATTERIES. THE DISTRIBUTOR/USER IS RESPONSIBLE TO KNOW THAT "SP ENT" & DAMAGED" BATTERIES ARE DISPOSED OF IN AN ENVIRONMENTALLY SOUND WAY IN ACCORDANCE WITH FEDE RAL, STATE & DISPOSED OF IN ROUTING NAME OF THE REGULATIONS.

Handling And Storage Precautions: HA

NDLING: DO NOT CARRY BATTERY BY TERMINALS.

DO NOT DROP BATTERY, PUNCTURE OR ATTEMPT TO OPEN BATTERY CASE. KEEP AWAY FROM FLAMES DURING AND IMMEDIATELY AFTER CHARGE. AVOID PROLONGED OVERCHARGES IN CONFINED AREAS.

Other Precautions: STORAGE: STORE AT AMBIENT ROOM TEMPERATURE. DO NOT SUBJECT PRODUCT TO OPEN FLAME OR FIRE. AVOID CONDITION WHICH COULD CAUSE ARCING BETWEEN BATTERY TERMINALS> HYGIENE: WASH HANDS THOROUGHLY BEFORE EATI NG OR SMOKING AFTER HANDLING BATTERIES.

========

Fire and Explosion Hazard Information

Extinguishing Media: MULTIPURPOSE DRY CHEMICAL OR MULTIPURPOSE CO2.

Fire Fighting Procedures: EVACUATE AREA. SELF-CONTAINED BREATHING APPARATUS MUST BE WORN TO PREVENT POSSIBLE INHALATION OF ACID MISTS, SMOKE AND DECOMPOSITION PRODUCTS IN A FIRE. REMOVE ALL IGNITION SOURCES. COOL BATTERY(S) TO PREVENT RUPTURE.

Unusual Fire/Explosion Hazard: HYDROGEN GA S MAY BE PRODUCED AND MAY EXPLODE IF

IGNITED. REMOVE ALL IGNITION SOURCES. VENTILATE AREA.

Control Measures

Respiratory Protection: NOT NECESSARY UNDER NORMAL CONDITIONS OF USE FOR FINISHED PRODUCT.

Ventilation: NOT NECESSARY UNDER NORMAL CONDITIONS OF USE FOR FINISHED PRODUCT.

Protective Gloves: NOT NECESSARY UNDER NORMAL CONDITIONS OF USE FOR FINISHED PRODUCT.

Eye Protection: NOT

NECESSARY UNDER NORMAL CONDITONS OF USE FOR FINISHED PRODUCT.

Work Hygienic Practices: NOT NECESSARY UNDER NORMAL CONDITONS OF USE FOR FINISHED PRODUCT.

Supplemental Safety and Health: OPTIMA BATTERIES ARE 100% RECYCLABLE BY ANY LICENSED RECLAMATION OPERATION.

Physical/Chemical Properties

HCC: Z4

Reactivity Data

=======

Stability Indicator: YES Stability Indicator: YES Stability Condition To Avoid: AVOID SHORTING, USE ONLY APPROVED CHARGING METHODS. DO NOT PUNCTURE BATTERY CASE. Hazardous Polymerization Indicator: NO Conditions To Avoid Polymerization: WILL NOT OCCUR.
Toxicological Information
======================================
======================================
Transport Information: DEALED LEAD ACID BATTERY IS NOT A DOT HAZARDOUS MATERIAL.
Regulatory Information
Federal Regulatory Information: ACCORDING TO THE OSHA HAZARD COMMUNICATION STANDARD, SE ALED LEAD ACID BATTERY IN ITS MANUFACTURER AND SUPPLIED STATE IS CONSIDERED NON-HAZARDOUS. State Regulatory Information: PROPOSITION 65 WARNING (CALIFORNIA): BATTERY POSTS, TERMINALS, AND RELATED ACCESSORIES CONTAIN LEAD AND LEAD COMPOUNDS, CHEMICALS KNOWN TO THE STATE OF CLAIFORNIA TO CAUSE CANCER AND REPRODUCTIVE HARM. WASH HANDS AFTER HANDLING.
Other Information
Other Info rmation: PER DOT, IATA, ICAO AND IMDG RULES AND REGULATIONS, THESE BATTERIES ARE EXEMPT FROM "UN2800" CLASSIFICATIONS AS A RESULT OF SUCCESSFUL COMPLETION OF THE FOLLOWING TESTS: 1) VIBRATION TESTS; 2) PRESSUR E DIFFERENTIAL TESTS; 3) CASE RUPTURING TESTS (NO FREE LIQUIDS). ALL BATTERIES

MUST BE IDENTIFIED AS "NON-SPILLABLE" OR "NON-SPILLABLE BATTERY" ON THE BATTERY AND THE SHIPMENT PER 49CFR173.159(D)(2) A ND BATTERY TERMINALS MUST BE PROTECTED FROM SHORT CIRCUITING.

______ Transportation Information _____ Responsible Party Cage: 0UJ55 Trans ID NO: 157974 Product ID: SEALED LEAD ACID BATTERY MSDS Prepared Date: 12/15/2000 Review Date: 07/24/2001 MFN: 1 Multiple KIT Number: 0 Review IND: Y Unit Of Issue: EA _____ Detail DOT Information _____ DOT PSN Code: ZZZ DOT Proper Shippi ng Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION _____ Detail IMO Information _____ IMO PSN Code: ZZZ IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION ______ **Detail IATA Information** _____ IATA PSN Code: ZZZ IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPO **RTATION** Detail AFI Information ______ AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

HAZCOM Label

Product ID: SEALED LEAD ACID BATTERY

Cage: 0UJ55

Company Name: OPTIMA BATTERIES INC

Street: 17500 E 22ND AVENUE

City: AURORA CO Zipcode: 8001

1

Health Emergency Phone: 800-434-9300

Label Required IND: Y

Date Of Label Review: 07/24/2001

Status Code: A
Origination Code: F
Eye Protection IND: NO
Skin Protection IND: NO
Signal Word: NONE

Respiratory Protection IND: NO

Health Hazard: None Contact Hazard: None Fire Hazard: None

Reactivity Hazard: None

Hazard And Precautions: EMERGENCY OVERVIEW: EXPOSURE NOT EXPECTED FOR PRODUCT UNDER NORMAL CONDITIONS OF USE. IN ITS MANUFACTURERED AND SUPPLIED STATE, THE PRODUCT IS CONSIDERED NON-HAZARD

OUS. KEEP AWAY FROM FLAMES DURING AN D

IMMEDIATELY AFTER CHARGE. NO SIGNIFICANT HEALTH EFFECTS ARE ASSOCIATED WITH THE PRODUCT.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or

viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of s

imilarity to a corresponding Department of Defense or other government situation.