

GREAT LAKES CHEMICAL CORP -- 045, HALON 1301 -- 6830-01-284-5852
===== Product Identification =====

Product ID:045, HALON 1301
MSDS Date:09/01/1990
FSC:6830
NIIN:01-284-5852
Status Code:A
MSDS Number: CLJXL
=== Responsible Party ===
Company Name:GREAT LAKES CHEMICAL CORP
Address:1801 HWY 52 NW
Box:2200
City:WEST LAFAYETTE
State:IN
ZIP:47996-2200
Country:US
Info Phone Num:765-497-6100/800-949-5167
Emergency Phone Num:(501) 862-5141
Preparer's Name:RESEARCH SERV
ICES DEPT
CAGE:2E394
=== Contractor Identification ===
Company Name:GREAT LAKES CHEMICAL CORP
Address:1801 HWY 52 NW
Box:2200
City:WEST LAFAYETTE
State:IN
ZIP:47996-2200
Country:US
Phone:765-497-6100/800-949-5167
CAGE:2E394
Company Name:KEYSTONE FIRE PROTECTION CO.
Address:108 PARK DRIVE, SUITE 3
Box:City:MONTGOMERYVILLE
State:PA
ZIP:18936
Country:US
Phone:215-641-0100/ FAX 215-641-9638
Contract Num:SP0450-00-D-0521
CAGE:1U693

===== Composition/Information on Ingredients =====

Ingred Name:BROMOTRIFLUOROMETHANE
CAS:75-63-8
RTECS #:PA5425000
OSHA PEL:6100 MG/M3;1000 PPM
ACGIH TLV:6090 MG/M3;1000 PPM
Ozone Depleting Chemical:1

===== Hazards Identification =====

LD50 LC50 Mixture:LC50 RAT >800,000 PPM FOR 4 HRS.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:HALON 1301 HAS ANESTHETIC AND CARDIAC
EFFECTS IN HUMANS AT CONCENTRATIONS ABOVE 1
0% BY VOLUME,
CONCENTRATIONS BELOW 10% ARE CONSIDERED SAFE FOR 0-5 MINUTE
EXPOSURES. HALON 1301 IS CLASSIFIED AS GROUP 6 (LEAST TOXIC) IN
THE UNDERWRITERS LABORATORIES CLASSIFICATION OF COMPARATIVE LIFE
HAZARDS OF FIRE EXTINGUISHING AGENTS. SMOKING IN AREAS WHERE THIS
CHEMICAL IS RELEASED CAN CAUSE FORMATION OF TOXIC & IRRITATING
HALOGENS AND HLOGEN ACIDS WHICH COULD BE INHALED WITH THE SMOKE.
Explanation of Carcinogenicity:PRODUCT IS NON-MUTAGENIC IN THE AMES
TEST.

Effects of Overexposure:THE ANESTHETIC EFFECT OF HALON 1301 AT LEVELS
BELOW 10% IS SIMILAR TO A FEELING OF MILD INTOXICATION. ANESTHETIC
EFFECTS END RAPIDLY AFTER EXPOSURE IS TERMINATED. PROLONGED
EXPOSURE TO CONCENTRATIONS ABOVE 10% (15-20%) MAY LEAD TO
UNCONSCIOUSNESS AND POSSIBLY DEATH. INHALATION OF PRODUCT & ITS
DECOMPOSITION PRODUCTS CAN CAUSE CLOUDING OF CONTACT LENSES.

Medical Cond Aggravated by Exposure:CARDIAC CONDITIONS MAY BE
AGGRAVATED BY OVEREXPOSURE.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE PERSON TO FRESH AIR; IF NOT BREATHING,
GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE
OXYGEN. GET MEDICAL ATTENTION. SKIN: FLUSH WITH WATER. GET MEDICAL
ATTENTION IF F ROSTBITE OCCURS. EYES: FLUSH WITH WATER. GET MEDICAL
ATTENTION. NOTE: EPINEPHRINE IS CONTRAINDICATED IN THE TREATMENT OF
OVER-EXPOSURE TO THIS PRODUCT.

===== Fire Fighting Measures ===

=====

Flash Point:NON-FLAMMABLE

Extinguishing Media:HALON 1301 IS A FIRE EXTINGUISHING AGENT. USE WATER SPRAY TO COOL CYLINDERS INVOLVED IN FIRES. USE MEDIA SUITABLE FOR FLAMMABLE MATERIAL IN THE AREA.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:PREDOMINANT DECOMPOSITION PRODUCTS ARE HYDROGEN FLUORIDE AND HYDROGEN BROMIDE IN FIRE SITUATIONS. THE PRODUCTS ARE IRRITATING AND POTENTIALLY TOXIC IF FIRE EXTINGUISHME

NT IS DELAYED. ABOVE 1000F, HALO N 1301 MAY RELEASE HYDROGEN FLUORIDE, HYDROGEN BROMIDE, CARBONYL FLUORIDE AND CARBONYL BROMIDE.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE AREA. WEAR SELF-CONTAINED BREATHING APPARATUS, VENTILATE ENCLOSED AREAS IN CASE OF DISCHARGE.

===== Handling and Storage =====

Handling and Storage Precautions:PROTECT CYLINDERS FROM PHYSICAL DAMAGE. STORAGE TEMPER
ATURE SHOULD NOT EXCEED 125F. CYLINDERS
SHOULD BE SECURED FOR STORAGE WITH VALVE PROTECTION CAP IN PLACE.

Other Precautions:DO NOT SMOKE OR WEAR CONTACT LENSES WHERE THIS PRODUCT IS BEING USED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR NIOSH APPROVED, SELF-CONTAINED BREATHING APPARATUS AT CONCENTRATIONS GREATER THAN 10,000 PPM AS RECOMMENDED BY NIOSH. CONSULT ANSI STANDARD AND OSHA REGULATIONS CONCERNING THE USE OF RESPI

RATORY EQUIPMENT. AVOID PROLONGED EXPOSURE TO EXCESSIVE CONCENTRATIONS.

Ventilation:LOCAL EXHAUST-MAERIAL TRANSFER AND HANDLING SHOULD BE CONDUCTED WITH AN EXHAUST SYSTEM. MECHANICAL-ALL INDOOR AREAS SHOULD BE WELL VENTILATED. SPECIAL-NONE

Protective Gloves:LINED NEOPRENE OR LEATHER IF FROSTBITE IS A POSSIBILITY

Eye Protection:CHEMICAL SAFETY GOGGLES IF FROSTBITE IS A POSSIBILITY.
DO NOT WEAR CONTACT LENS

Other Protective Equipment:NONE

Work Hygienic Practices:DETERMINE THAT

PIPING IS EMPTY BEFORE DOING
MAINTENANCE WORK. PERIODICALLY CHECK CYLINDER TO ENSURE VALVES ARE
NOT LEAKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:G3
Boiling Pt:=-57.6C, -72.F
Melt/Freeze Pt:=-167.6C, -270.F
Vapor Pres:6200 AT 0C
Vapor Density:5.1
Spec Gravity:1.57 AT 20C
Evaporation Rate & Reference:NOT AVAILABLE
Solubility in Water:0.03% BY WEIGHT
Appearance and Odor:ODORLESS, COLORLESS GAS

===== Stab
ility and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
ACTIVE METALS, FIRES OF METAL HYDRIDES, AND MATERIAL CONTAINING OWN
OXYGEN. PRODUCT WILL NOT EXTINGUISH FIRES OF THESE MATERIALS.
PRODUCT MAY DEGRADE CERTAIN POLYMERIC MATERIALS.
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:IN THE PRESENCE OF FLAMES OR HOT
SURFACES: HYDROGEN FLUORIDE, HYDROGEN BROMIDE, BROMINE, CARBONYL
FLUORIDE, AND CARBONYL BROMIDE. SMOKING CAN CAUSE F
ORMATION OF
THESE CHEMCIALS AND MUST BE AVOIDED IN
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Toxicological Information =====

Toxicological Information:APPROXIMATE LETHAL CONCENTRATION OF HALON
1301 TO THE RAT IS GREATER THAN 800,000 PPM FOR 15 MINUTES. THE
ACUTE INHALATION LC50 WITH RATS IS GREATER THAN 800,000 PPM FOR 4
HOURS. THE COMPOUND IS REPOR TED TO BE NON-MUTAGENIC IN THE AMES
TEST. HALON 1301 HAS ANESTHETIC AND CARDIAC EF
FECTS IN HUMANS AT
CONCENTRATIONS ABOVE 10% BY VOLUME, CONCENTRATIONS BELOW 10% ARE
CONSIDERED SAFE FOR 0-5 MINUTE EXP OSURES.

===== Disposal Considerations =====

Waste Disposal Methods:RETURN CYLINDERS TO GREAT LAKES CHEMICAL
CORPORATION, EL DORADO, ARKANSAS.

===== MSDS Transport Information =====

Transport Information:DOT: COMPRESSED GAS, N.O.S.
(BROMOTRIFLUOROMETHANE) NON-FLAMMABLE GAS, UN 1956. EXPORT:
BR

OMOTRIFLUOROMETHANE, NON-FLAMMABLE GAS, UN 1009, IMO CLASS 2.2.

===== Regulatory Information =====

SARA Title III Information:THIS CHEMICAL IS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF SUPERFUND AND 40 CFR 372.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.