View NSN Online: https://aerobasegroup.jp/nsn/5920-01-238-7449 DEL PAINT MFG -- LATEX PROLINE WHITE -- 5920-01-238-7449 ============ Product Identification ========================= Product ID:LATEX PROLINE WHITE MSDS Date:06/21/1999 FSC:5920 NIIN:01-238-7449 Status Code:A MSDS Number: CLLZF === Responsible Party === Company Name: DEL PAINT MFG Address:3105 EAST RENO City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Info Phone Num: 405-672-1431 Emergency Phone Num:1-800-424-9300 Preparer' s Name: ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300 CAGE:39934 === Contractor Identification === Company Name: DEL PAINT MFG Address:3105 EAST RENO Box:City:OKLAHOMA CITY State:OK ZIP:73117 Country:US Phone: 405-672-1431 CAGE:39934 ======= Composition/Information on Ingredients ======== Ingred Name: ETHYLENE GLYCOL CAS:107-21-1 RTECS #: KW2975000 = Wt:.94ACGIH STEL:C127 MG/M3;C50 PPM EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

========== Hazards Identification ===========

Routes of Entry: Inhalation:UNKNOWN Skin:UNKNOWN Ingestion:YES Effects of Overexposure:MAY CAUSE SOME NAUSEA IF INGESTED.
======================================
First Aid:IF INGESTED: GIVE 2 GLASSES OF WATER AND INDUCE VOMITING BY PUTTING FINGER DOWN THROAT. SKIN: FLUSH WITH WATER. EYES FLUSH WITH WATER.
======================================
Flash Point Method:TCC Flash Point:=116.1C, 241.F Lower Limits:3.2% Exting
uishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, Unusual Fire/Explosion Hazard:THE PRODUCT WILL NOT BURN UNTIL WATER HAS EVAPORATED.
========= Accidental Release Measures ==========
Spill Release Procedures:MAJOR SPILLS SHOULD BE COLLECTED FOR DISPOSAL.
======================================
Handling and Storage Precautions:STORE ABOVE 32 F. Other Precautions:DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.
=====
===== Exposure Controls/Personal Protection ========
Respiratory Protection:APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVER-SPRAY DURING SPRAY APPLICATION. Ventilation:NORMAL SUCH AS FAN. Protective Gloves:PROTECTIVE GLOVES: DESIRABLE. Eye Protection:SAFETY GLASSES.
Other Protective Equipment:EYE BATH. Work Hygienic Practices:WASH HANDS AND FACE BEFORE EATING. Supplemental Safety and Health
========= Physical/Chemical Properties ======

========

Boiling Pt:B.P. Text:212-387 F Vapor Density:HEAVIER Evaporation Rate & Deference: SLOWER THAN ETHER Percent Volatiles by Volume:71.63%

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products: RESIDUALS CAN BURN AND PRODUCE CARBON MONOXIDE & CARBON DIOXIDE.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

======= Disposal Considerations ============

Waste Disposa

I Methods:BURY IN A LANDFILL WHERE PERMITTED UNDER APPROPRIATE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.