

View NSN Online: <https://aerobasegroup.jp/nsn/6685-01-064-7990>

DEFENSE SUPPLY CENTER RICHMOND, ATTN: DSCR-VBA -- NITROGEN, COMPRESSED, (SEE SUPPL) -- 4920-01-064-7990

===== Product Identification =====

Product ID:NITROGEN, COMPRESSED, (SEE SUPPL)

MSDS Date:09/27/2001

FSC:4920

NIIN:01-064-7990

Status Code:A

Kit Part:Y

MSDS Number: CLMPX

=== Responsible Party ===

Company Name:DEFENSE SUPPLY CENTER RICHMOND, ATTN: DSCR-VBA

Address:8000 JEFFERSON DAVIS HIGHWAY

Ci

ty:RICHMOND

State:VA

ZIP:23297-5607

Country:US

Info Phone Num:804-279-4371, DSN 695-4371

Emergency Phone Num:804-279-4371

Preparer's Name:DSCR-VBA

CAGE:SO004

=== Contractor Identification ===

Company Name:DEFENSE SUPPLY CENTER RICHMOND, ATTN: DSCR-VBA

Address:8000 JEFFERSON DAVIS HIGHWAY

Box:City:RICHMOND

State:VA

ZIP:23297-5607

Country:US

Phone:804-279-4371, DSN 695-4371

CAGE:SO004

===== Composition/Information on Ingredients =====

Ingred Name:NITROGEN

CAS:7727-37-9

RTECS #:

QW9700000
= Wt:100.
Code:F
ACGIH TLV:ASPHYXIAN; 9596

===== Hazards Identification =====

LD50 LC50 Mixture:NOT RELEVANT
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS: LUNGS, CNS. ACUTE-
ASPHYXIAN. INHALATION: AT 2-3% CONCENTRATION, SYMPTOMS OF ASPHYXIA
OCCURS; 3-5% CAUSES INCREASED RESPIRATION AND HEADACHE; UP TO 15%
CAUSES UNCONSCIOUSNESS.
HIGHER C ONCENTRATIONS CAUSE RAPID
CIRCULATORY INSUFFICIENCY LEADING TO COMA AND DEATH. EYE/SKIN/ORAL:
UNLIKELY (GAS). CHRONIC- UNKNOWN.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:HEADACHE, RAPID RESPIRATION, REDUCED
CONSCIOUSNESS OF SURROUNDINGS, RINGING IN THE EARS, LOSS OF BALANCE
OR DIZZINESS, TINGLING OF THE TONGUE, FINGERTIPS OR TOES, TIGHTNESS
IN THE FRONTAL AREA OF THE FOREHEAD, WEAKENED SPEECH LEADING TO
THE INABILITY TO UTTER SOUNDS, NAUSEA, UN
CONSCIOUSNESS, DEATH

===== First Aid Measures =====

First Aid:PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF
OVEREXPOSURE. RESCUE PERSONNEL SHOULD WEAR SELF-CONTAINED BREATHING
APPARATUS. INHALED:REMOVE TO FRESH AIR. PROVIDE OXYGEN/CPR IF
NEEDED. EYE/SKIN /ORAL: UNLIKELY (GAS)

===== Fire Fighting Measures =====

Flash Point:NONE
Lower Limits:NOT RELEVANT
Upper Limits:NOT RELEVANT
Extinguishing Media:USE
WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL FOR SURROUNDING FIRE. KEEP FIRE-EXPOSED CYLINDERS COOL
WITH WATER.
Fire Fighting Procedures:AS WITH ANY FIRE, WEAR PROTECTIVE CLOTHING AND
NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS IF NEEDED.
Unusual Fire/Explosion Hazard:CYLINDERS MAY RUPTURE VIOLENTLY.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL PERSONNEL FROM AFFECTED AREA. USE
APPROPRIATE PROTECTIVE EQUIPM

ENT. VENTILATE AREA. IF LEAK IS FROM
CYLINDER OR ITS VALVE, CONTACT SUPPLIER. THE ATMOSPHERE MUST HAVE
AT LEAST 19.5% OXYGEN BEFORE PERSONNEL CAN BE ALLOWED IN THE AREA.
Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE CYLINDERS UPRIGHT, SECURE, IN
COOL, DRY, VENTILATED AREA BELOW 125F. PROTECT FROM PHYSICAL
DAMAGE. FULL AND EMPTY CYLINDERS SHOULD BE SEGREGATED.

Other Precautions:AVOID BREATHING GASES. KEEP OUT OF REACH OF CHILDREN.
USE IN WELL VENTILATED AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF OXYGEN LEVEL IS BELOW 19.5%, USE
NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED AIR
RESPIRATOR, OPERATED IN POSITIVE PRESSURE MODE.

Ventilation:ADEQUATE

Protective Gloves:LEATHER WHEN HANDLING CYLINDERS

Eye Protection:GOGGLES/GLASSES RECOMMENDED

Other Protective Equipment:SAFETY SHOES WHEN HANDLING CYLINDERS

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES.

Supplemental Safety and Health

THIS ENTRY DESCRIBES THE COMPRESSED NITROGEN, PART OF PRESSURE CONTROL
AND ACCESSORY GROUP FOR THE END ITEM: TEST SET FOR ACFT F-16.

===== Physical/Chemical Properties =====

HCC:G3

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:-320F,-196C

Melt/Freeze Pt:M.P/F.P Text:-346F,-210C

Vapor Density:0.97

Spec Gravity:0.8083 (LIQUID)

Viscosity:NOT RELEVANT

Evaporation Rate & Reference:NOT RELEVANT (GAS)

Solubility in Water:VERY SLIGHT

Appearance and Odor:COLORLESS GAS - ODORLESS

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE

Stability Condition to Avoid:HEATING CYLINDER

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT ATTEMPT TO

DISPOSE OF RESIDUAL OR UNUSED
QUANTITIES. RETURN IN THE SHIPPING CONTAINER PROPERLY LABELED, WITH
ANY VALVE OR CAPS SECURED TO YOUR SUPPLIER FOR PROPER DISPOSAL.

===== MSDS Transport Information =====

Transport Information:PROPER SHIPPING NAME: NITROGEN; UN 1066.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no man
ner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.