View NSN Online: https://aerobasegroup.jp/nsn/6850-01-411-7451

\_\_\_\_\_\_

ECOLINK INC	0301-1,QED
ECOLINK INC	0301-1,QEE

MSDS Safety Information

FSC: 6850 NIIN: 01-411-7451 MSDS Date: 01/25/2000 MSDS Num: CLNJR Product ID: 0301-1,QED MFN: 01 Responsible Party Cage: 0WU71 Name: ECOLINK INC Address: 1481 ROCK MOUNTAIN BLVD City: STONE MOUNTAIN GA 30083-1505 Info P hone Number: 800-886-8240/770-621-8240 Emergency Phone Number: 800-877-3339(8-5 EST)/800-535-5053
Item Description Information
Item Manager: S9G Item Name: CLEANING COMPOUND,SOLVENT Specification Number: UNKNOWN Unit of Issue: BX Quantitative Expression: 0000000004EA UI Container Qty: 1 Type of Container: CONTAINER
Ingredients
======================================
Health Hazards Data
LD50 LC50 Mixture: NOT PROVIDED Route Of Entry Inds - Inhalation: YES Skin: YES Ingestion: YES Carcinogenicity Inds - NTP: NO IARC: NO OSHA: NO Effects of Exposure: INGESTION: SWALLOWING LARGE AMOUNTS MAY BE HARMFUL, BY CAUSING GASTROINTESTINAL IRRITAT

ION. INHALTION: BREATHING LARGE AMOUNTS MAY

BE HARMFUL, BY CAUSING NOSE, THROAT, RESPIRATORY TRACT IRRITATION. EY ES: IRRITANT. LIQUID CONTACT WILL IRRITATE EYES AND MAY CAUSE STINGING, TEARING, AND REDNESS. SKIN CONTACT: MAY CAUSE MILD IRRITATION OF REDNESS AND BURNING. Explanation Of Carcinogenicity: NONE

Signs And Symptions Of Overexposure: INGESTION: MAY CAUSE GASTROINTESTINAL IRRITATION. INHALTION: BREATHING LARGE AMOUNTS MAY CAUSE NOSE, THROAT, RESPIRATORY TRACT IRRITATION. EYES:

IRRITANT. LIQUID CONTACT WILL IRRITATE

EYES AND MAY CAU SE STINGING, TEARING, AND REDNESS. SKIN CONTACT: MAY CAUSE MILD IRRITATION OF REDNESS AND BURNING.

Medical Cond Aggravated By Exposure: NOT PROVIDED

First Aid: INGESTION: SEEK MEDICAL ATTENTION IMMEDIATELY. IF INDIVIDUAL IS DROWSY OR UNCONSCIOUS DO NOT GIVE ANYTHING BY MOUTH; PLACE INDIVIDUAL ON LEFT SIDE WITH HEAD DOWN. CONTACT MEDICAL FACILITY OR POISON CO NTROL CENTER FOR ADVICE ABOUT WHETHER TO INDUCE VOMITING. INHALTION: REM

OVE TO FRESH AIR, IF

BREATHING IS DIFFICULT GIVE OXYGEN. KEEP PERSON WARM AND QUIET. SEEK MEDICAL ATTENTION. EYES: IRRIGATE IMME DIATELY WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. SKIN: WASH WITH SOAP AND WATER. THOROUGHLY CLEAN CONTAMINATED CLOTHES AND SHOES BEFORE REUSE. IF SYMPTOMS PERS IST, SEEK MEDICAL ATTENTION.

\_\_\_\_\_

Handling and Disposal

\_\_\_\_\_

==

Spill Release Procedures: SMALL: ADSORB LIQUID ON VERMICULITE, FLOOR ABSORBENT/OR OTHER ABSORBENT MATERIAL AND TRANSFER TO HOOD. LARGE: ELIMINATE IGNITION SOURCES (FLARES, FLAMES, INCLUDING PILOT LIGHTS, ELECTRICAL SPARKS). MA KE SURE AREA IS WELL VENTILATED. PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN COMPLETED. STOP SPILL AT SOURCE. PREVENT FROM ENTERING DRAINS.

Neutralizing Agent: NOT RELEVANT

Waste Disposal Methods: QED

LIQUID IS TO BE DISPOSED OF ACCORDING TO LOCAL, S

TATE AND FEDERAL REGULATIONS. PLEASE CALL US IF YOU NEED ADDITIONAL DISPOSAL INFORMATION. UNDER RCRA THIS MATERIAL IS CONSIDERED A HAZARDOUS WASTE DUE TO THE FLASH POINT. THE EPA HAZARDOUS WASTE NUMBER IS D001.

Handling And Storage Precautions: EMPTY CONTAINERS CONTAIN PRODUCT RESIDUE AND MAY BE UNDER PRESSURE, ALL HAZARD PRECAUTIONS GIVEN IN THE MATERIAL SAFETY DATA SHEET MUST BE OBSERVED. ANY USE OF THIS PRODUCT IN ELEVATED TEMPERATU RE

PRO CESSES SHOULD BE THOROUGHLY EVALUATED TO ESTABLISH AND MAINTAIN SAFE OPERATING CONDITIONS.

Other Precautions: KEEP THIS AND ALL CHEMICALS OUT OF THE REACH OF CHILDREN.

\_\_\_\_\_

Fire and Explosion Hazard Information

\_\_\_\_\_ Flash Point Method: TCC Flash Point: =40.C. 104.F Lower Limits: 1.2 Upper Limits: 9.6 Extinguishing Media: REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICAL, CLASS B, WATER FO G Fire Fighting Procedures: KEEP FIRE EXPOSED CONTAINERS COOL WITH WATER. FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WITH APPROPRIATE GEAR AND CHEMICAL RESISTANT PERSONAL PROTECTIVE EQUIPMENT. Unusual Fire/Explosion Hazard: VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR BE MOVED BY VENTILATION AND IGNITED BY HEAT, PILOT LIGHTS, OTHER FLAMES AND IGNITION SOURCES AT LOCATIONS DISTANT F ROM MATERIAL HANDLING POINT. NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT CAN IGNITE EXPLOSIVELY. \_\_\_\_\_ **Control Measures** Respiratory Protection: NOT REQUIRED UNDER CONDITIONS OF NORMAL. IF VAPOR MIST IS PRESENT USE NIOSH CERTIFIED ORGANIC VAPOR MASK. Ventilation: LOCAL EXHAUST/HOOD OR FAN MAY BE USED. Protective Gloves: NITRILE GLOVES **Eye Protection** : SAFETY GLASSES AND SPLASH PROTECTION REQUIRED Other Protective Equipment: NONE REQUIRED UNDER NORMAL USE. Work Hygienic Practices: STORE RAGS USED WITH THIS MATERIAL IN AN AIR TIGHT, METAL CONTAINER TO PREVENT SPONTANEOUS COMBUSTION. TREAT THIS CHEMICAL WITH RESPECT AND FOLLOW ALL MSDS INSTRUCTIONS. Supplemental Safety and Health: SYNONYM: SYNTHETIC ISOPARAFFINIC HYDROCARBON. ABBREVIATION: N/A = NOT APPLICABLE, N/AV = NOT AVAILABLE, N/K = UNKNOWN, N/P = NOT PROVIDED. N/R = NOT RELEVANT

. N/D = NOT DETERMINED. N/E = NOT ESTABLISH ED. CNS = CENTRAL NERVOUS SYSTEM. GI = GASTROINTESTINAL. SCBA = SELF CONTAINED BREATHING APPARATUS. \_\_\_\_\_ Physical/Chemical Properties \_\_\_\_\_ HCC: F4 NRC/State LIC No: NOT RELEVANT Boiling Point: =160.C, 320.F B.P. Text: @760MMHG Decomp Text: NOT PROVIDED Vapor Pres: 2MMHG @68F Vapor Density: 4.94 Spec Gravity: 0.750 Viscosity: NOT PROVIDED Solubilit y in Water: NEGLIGIBLE Appearance and Odor: CLEAR, COLORLESS LIQUID WITH MILD PETROLEUM ODOR Percent Volatiles by Volume: NOT PROVIDED Corrosion Rate: NOT PROVIDED \_\_\_\_\_ Reactivity Data \_\_\_\_\_ Stability Indicator: YES Stability Condition To Avoid: SOURCES OF IGNITION SUCH AS SPARKS, HOT SPOTS, WELDING FLAMES AND CIGARETTES. IGNITION/FLASH MAY RESULT IF CONCENTRATION OF PRODUCT IS IN FLAMMABLE RANGE. Materials To Avoid: IF MIXED WITH STRONG OXIDIZERS AND/OR ACIDS THERE IS THE POSSIBILITY OF A DAMGEROUS CHEMICAL REACTION. Hazardous Decomposition Products: MAY FOR CARBON DIOXIDE AND CARBON MONOXIDE. Hazardous Polymerization Indicator: NO Conditions To Avoid Polymerization: NONE \_\_\_\_\_ Toxicological Information \_\_\_\_\_ Toxicological Information: NOT PROVIDED \_\_\_\_\_ \_\_\_\_\_ Ecological Information \_\_\_\_\_ Ecological: NOT PROVIDED \_\_\_\_\_ **MSDS** Transport Information \_\_\_\_\_ Transport Information: DOT REGULATED: NO \_\_\_\_\_ **Regulatory Information** 

Federal Regulatory Information: ALL MATTERIALS IN PRO

DUCT ARE TSCA LISTED. State Regulatory Information: NOT PROVIDED

\_\_\_\_\_

## Other Information

\_\_\_\_\_

Other Information: SUDDEN RELEASE OF HOT ORGANIC CHEMICAL VAPORS OR MISTS FROM PROCESS EQUIPMENT OPERATING AT ELEVATED TEMPERATURES MAY RESULT IN IGNITION.

\_\_\_\_\_

## Transportation Information

\_\_\_\_\_\_

Respon sible Party Cage: 0WU71 Trans ID NO: 159268 Product ID: 0301-1,QED MSDS Prepared Date: 01/25/2000 Review Date: 10/12/2001 MFN: 1 Tech Entry NOS Shipping Nm: ISOPARFFINIC HYDROCARBON (64742-48-9) > 85 % Net Unit Weight: 6.2 LBS Limited Quantity IND: Y Multiple KIT Number: 0 Unit Of Issue: BX Container QTY: 1 Type Of Container: CONTAINER Additional Data: LIMITED QUANTITIES ARE EXCEPT FROM LABELING, PLACARDING AND SPECIFICATION PACKAGING; UNLESS SHIPPED BY AIR (SEE 49 CFR 173.150). \_\_\_\_\_ \_\_\_\_\_ Detail DOT Information \_\_\_\_\_ DOT PSN Code: LKZ DOT Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S. OR PETROLEUM PRODUCTS, N.O.S. Hazard Class: 3 UN ID Num: UN1268 DOT Packaging Group: III Label: FLAMMABLE LIQUID Special Provision: B1,T7,T30 Packaging Exception: 150 Non Bulk Pack: 203 Bulk Pack: 242 Max Qty Pass: 60 L Max Qty Cargo: 220 L Vessel Stow Reg: A \_\_\_\_\_

\_\_\_\_\_ IMO PSN Code: LMH IMO Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S. o IMDG Page Number: 3375 UN Number: 1268 UN Hazard Class: 3.3 IMO Packaging Group: III Subsidiary Risk Label: -EMS Number: 3-07 MED First Aid Guide NUM: 311 \_\_\_\_\_ Detail IATA Information \_\_\_\_\_ IATA PSN Code: TJB IATA UN ID Num : 1268 IATA Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S. IATA UN Class: 3 IATA Label: FLAMMABLE LIQUID UN Packing Group: III Packing Note Passenger: 309 Max Quant Pass: 60L Max Quant Cargo: 220L Packaging Note Cargo: 310 \_\_\_\_\_ Detail AFI Information \_\_\_\_\_ AFI PSN Code: TJB AFI Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S. AFI Hazard Class: 3 AFI UN ID NUM: UN1268 AFI Packing Group: I Ш **Special Provisions: P5** Back Pack Reference: A7.3 \_\_\_\_\_ HAZCOM Label \_\_\_\_\_ Product ID: 0301-1,QED Cage: 0WU71 **Company Name: ECOLINK INC** Street: 1481 ROCK MOUNTAIN BLVD **City: STONE MOUNTAIN GA** Zipcode: 30083-1505 Health Emergency Phone: 800-877-3339(8-5 EST)/800-535-5053 Label Required IND: Y Date Of Label Review: 10/12/2001 Status Code: A MFG Label NO: NOT PROVIDED Label Date: 01/25/2000 Year P

rocured: 2002 Origination Eye Protection IND: YES Skin Protection IND: YES Signal Word: WARNING **Respiratory Protection IND: NO** Health Hazard: Slight Contact Hazard: Slight Fire Hazard: Moderate Reactivity Hazard: None Hazard And Precautions: TARGET ORGANS: N/P. KEEP OUT OF REACH OF CHILDREN. INGESTION MAY CAUSE GI IRRITATION. BREATHING MAY CAUSE NOSE, THROAT, RESPIRATORY IRRITATION. EYE IRRITANT. MAY CAUSE MILD SKIN IRRITATION, REDNESS AN D BURNING. FIRST AID: INGESTION: SEEK MEDICAL ATTE NTION IMMEDIATELY. INHALTION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT GIVE OXYGEN. SEEK MEDICAL ATTENTION. EYES: IRRIGATE IMMEDIATELY WITH WATE R FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. SKIN: WASH WITH SOAP AND WATER. IF SYMPTOMS PERSIST, SEEK MEDICAL ATTENTION. SPILL: ADSORB ON Disclaimer (provided with this informa tion by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

VERMICULITE, FLOOR ABSORBENT/ OTH ER ABSORBENT MATERIAL AND TRANSFER TO HOOD.

The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person

utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.